

# 2012

## OPERATOR'S MANUAL

### CROSSOVER/MOUNTAIN/ PERFORMANCE MODELS

F 800 LXR/Sno Pro  
F 1100 LXR/Sno Pro/LTD  
F 1100 Turbo LXR/Sno Pro/LTD  
M 800/Sno Pro/HCR  
M 1100/Sno Pro/LTD  
M 1100 Turbo/Sno Pro/LTD/HCR  
XF 800 LXR/Sno Pro/High Country  
XF 1100 LXR/Sno Pro/LTD  
XF 1100 Turbo LXR/Sno Pro/LTD



**ARCTIC CAT®**  
SHARE OUR PASSION.™



## Limited Warranty

Arctic Cat Inc. (hereinafter referred to as Arctic Cat) extends a limited warranty on each new Arctic Cat Snowmobile it assembles and on each part and accessory assembled or sold by Arctic Cat. The warranty is extended to the original retail purchaser only on parts and accessories sold through an authorized Arctic Cat Snowmobile dealer. Warranty on snowmobiles is extended to the original retail purchaser; however, the balance of the unused warranty may be transferred to another party. Warranty coverage is only available in the country in which the original retail purchase occurs to the original retail purchaser resident in that country or to a transferee resident in that country of the balance of the unused warranty.

Arctic Cat warrants only the products it assembles and/or sells and does not warrant that other products will function properly when used with an Arctic Cat Snowmobile or will not damage the Arctic Cat Snowmobile. Arctic Cat does not assume any liability for incidental or consequential damages.

Arctic Cat will repair or replace, at its option, free of charge (including any related labor charges), any parts that are found to be warrantable in material or workmanship. This repair work MUST be done by an authorized Arctic Cat Snowmobile dealer. No transportation charges, rental charges, or inconvenience costs will be paid by Arctic Cat. The warranty is validated upon examination of said parts by Arctic Cat or an authorized Arctic Cat Snowmobile dealer. Arctic Cat reserves the right to inspect such parts at its factory for final determination if warranty should apply.

The warranty periods are as follows:

1. For snowmobiles used for recreational purposes:
  - If purchased between May 1 and November 30, warranty expires ONE (1) YEAR from December 1 of the current year.
  - If purchased between December 1 and April 30, ONE (1) YEAR from the date of sale.
2. For snowmobiles used for commercial purposes (including rental operations), ONE (1) YEAR from the date of invoice and/or 5000 MILES whichever comes first (non-transferable).
3. THIRTY (30) DAYS from date of sale of snowmobile on Arctic Cat supplied batteries.
4. THIRTY (30) DAYS from date of sale for all dealer installed genuine Arctic Cat service parts and accessories.
5. UNTIL EXPIRATION OF THE NEW PRODUCT WARRANTY (paragraphs 1 and 2 above) for all eligible replacement parts on new product.

Exclusions to this warranty include normal wear, abuse (i.e. a track run on marginal snow conditions without proper lubrication or additional idler wheels), and the following parts:

Fuel Filter	Light Bulbs	Windshield	Drive Belt	Torn or Punctured Upholstery
Wear Bars	Brake Pads	Spark Plugs	Drive Clutch/Driven Pulley	Wear Parts
Wear Strips	Shock Absorber(s) - Standard*	Shock Absorber(s) - Rebuildable**		
* Limited to one (1) year or 1000 miles of "normal" riding conditions - replace for defective or leaking shock, corroded or pitted shaft, peeling chrome.				
** Limited to one (1) year or 1000 mile of "normal" riding conditions - rebuild for leaking shock (warranted) - replace for defective shock, corroded or pitted shaft, peeling chrome.				

The following will VOID Arctic Cat's warranty:

1. Failure to perform the proper break-in procedure and all related maintenance, storage procedures (if stored for extended periods), and/or service as recommended in the Operator's Manual.
2. Repairs and/or adjustments by anyone other than an authorized Arctic Cat Snowmobile dealer.
3. Use of an improper fuel mixture ratio.
4. Use of improper carburetor main jets.
5. Use of improper gasoline, lubricating oils, or spark plugs.
6. An accident or subjecting the snowmobile to misuse, abuse, or negligent operation.
7. Any modification, addition, or removal of parts unless instructed to do so by Arctic Cat.
8. Use of the snowmobile in any way for racing purposes.
9. Removal of the engine for use in another vehicle.
10. Removal or mutilation of the Vehicle Identification Number or Engine Serial Number.
11. Use of parts not sold or approved by Arctic Cat.
12. Track and tunnel damage resulting from either ice stud or hooker plate installation.
13. Damage due to improper transportation.

In consideration of the foregoing, any implied warranty is limited in duration to the various warranty periods set forth. This warranty gives you specific legal rights, and you may also have other rights which vary from state/province to state/province and country to country. Some jurisdictions do not allow limitations on how long an implied warranty lasts, so the above limitations may not apply to you.



## Table of Contents

Limited Warranty .....	Inside Front Cover	Emergency Stopping.....	26
Foreword .....	1	Throttle/Ignition Monitor Switch .....	26
Declaration of Conformity .....	2	Varying Altitude Operation .....	27
Snowmobile Safety Rules .....	3	Lubrication .....	29-30
General Information .....	4-23	Chain Case .....	29
Snowmobile Identification .....	4	Rear Suspension.....	30
Control Locations .....	4	Maintenance .....	31-53
Gasoline-Oil .....	5	Periodic Maintenance Checklist.....	31
Engine Break-In .....	6	Air Cleaner/Filter (1100 cc Turbo Models).....	32
Drive Belt Break-In .....	6	Fuel System .....	32
Cold Drive-Away Function (1100 cc Models) .....	7	Checking Engine Oil Level (1100 cc Models)....	33
Speedometer/Tachometer.....	7	Changing Engine Oil/Filter (1100 cc Models)....	33
Diagnostic Codes .....	12	Coolant Level .....	35
Handlebar Height/Tilt (M 800 Sno Pro/LTD/ HCR/XF 800 High Country Models) .....	13	Spark Plugs.....	35
Handlebar Tilt.....	13	Checking/Adjusting Valve Clearance (1100 cc Models).....	37
Speedometer/Tachometer Angle.....	14	Checking/Adjusting APV Cables (800 cc Models).....	37
Exhaust System .....	14	Battery (Electric Start).....	38
Air-Intake Silencer.....	14	Fuses .....	40
Cooling System .....	14	Brake System.....	41
Battery (Electric Start).....	14	Burnishing Brake Pads.....	44
Jump-Starting (1100 cc Models) .....	15	Drive Belt.....	44
Drive Clutch and Driven Pulley .....	16	Track Tension .....	46
Drive Clutch/Driven Pulley Alignment.....	16	Track Alignment.....	47
Fuel Pump.....	16	Suspension .....	48
Shock Absorbers.....	17	Lights.....	51
Standard Track (XF/F Models) .....	17	Ski Wear Bars .....	52
Paddle Track (XF High Country/M Models) .....	17	Adjusting Ski Stance (M/XF Models).....	53
Track Studs (XF/F Models).....	17	Rail Wear Strips .....	53
Reverse Operation .....	18	Performance Tips.....	54-55
Access Panel/Hood (Removing/Installing) .....	20	Preparation for Storage.....	56-57
Removable Seat.....	21	Preparation after Storage.....	58
Towing .....	21	U.S. EPA Emission Control Statement/Warranty Coverage (U.S. Only) .....	59
Arctic Power Valve (APV) System (800 cc Models).....	22	Change of Address, Ownership, or Warranty Transfer.....	61
Exhaust Controlled Timing (ECT) System (800 cc Models).....	22	Warranty Procedure/Owner Responsibility .....	Inside Back Cover
Operating Instructions.....	24-28		
Starting and Stopping Engine .....	24		
Braking .....	25		



## Reference Information

Write the appropriate information for your Arctic Cat Snowmobile in the spaces below.

Always use these numbers when referring to your snowmobile.

Model: \_\_\_\_\_

Date of Purchase: \_\_\_\_\_

Vehicle Identification Number: \_\_\_\_\_

Engine Serial Number: \_\_\_\_\_

**Your Arctic Cat Dealer:** \_\_\_\_\_

**Address:** \_\_\_\_\_

**Phone:** \_\_\_\_\_

### **WARNING**

**A snowmobile is a very high performance vehicle. Because it does accelerate rapidly and is capable of very high speeds, it should not be operated by a novice or an inexperienced operator. Never accelerate rapidly or drive at high speed beyond the limits of visibility or without being totally familiar with the terrain and what lies in front of you. Obey speed limits and never operate at speeds that do not allow adequate maneuvering and stopping distances. Read and study the entire Operator's Manual and Safety Handbook. Failure to follow this warning could result in personal injury to yourself or others.**

### **Personal Injury**

- To avoid injury to yourself and others, NEVER operate the snowmobile without first reading and understanding this manual and the Snowmobile Safety Handbook; then follow the instructions and heed the warnings given.
- USE COMMON SENSE.
- DON'T DRINK and DRIVE.
- STAY IN CONTROL at ALL TIMES.
- TELL YOUR FRIENDS. If you see a friend operating a snowmobile recklessly, at excessive speeds, while intoxicated, or in other unsafe ways, don't wait until it is too late to warn of the consequences of snowmobile misuse. Such conduct endangers everyone. TAKE AN ACTIVE ROLE IN THE SAFETY OF YOURSELF AND OTHERS.



### **Parts and Accessories**

When in need of replacement parts, oil, or accessories for your Arctic Cat Snowmobile, be sure to only use GENUINE ARCTIC CAT PARTS, OIL, AND ACCESSORIES. Only genuine Arctic Cat parts, oil, and accessories are engineered to meet the standards and requirements of your Arctic Cat Snowmobile. For a complete list of accessories, refer to the current Arctic Cat Accessory Catalog. To aid in service and maintenance procedures on these snowmobiles, an Illustrated Parts Manual and a Service Manual are available through your local Arctic Cat Snowmobile dealer.



## Foreword

Congratulations! You have chosen a quality Arctic Cat Snowmobile designed and assembled to give dependable service. Be sure, as the owner/operator of an Arctic Cat Snowmobile, to become thoroughly familiar with its basic operation, maintenance, and off-season storage procedures. Read this manual and the accompanying Snowmobile Safety Handbook before operating the snowmobile to learn safe and proper use of your new Arctic Cat Snowmobile. Always operate the snowmobile within your level of skill and current terrain conditions.

The Operator's Manual, Snowmobile Safety Handbook, and Snowmobile Decals display the words Warning, Caution, and Note to emphasize important information. The symbol  **WARNING** identifies personal safety-related information. Be sure to follow the directive because it deals with the possibility of serious personal injury or even death. A **CAUTION** identifies unsafe practices which may result in snowmobile-related damage. Follow the directive because it deals with the possibility of damaging part or parts of the snowmobile. The symbol  **NOTE:** identifies supplementary information worthy of particular attention.

This manual covers operator-related maintenance, operating instructions, and off-season storage instructions. If major repair or service is ever required, contact an authorized Arctic Cat Snowmobile dealer for professional service.

At the time of publication, all information and illustrations were technically correct. Some illustrations used in this manual are used for clarity purposes only and are not designed to depict actual conditions. Because Arctic Cat Inc. constantly refines and improves its products, no retroactive obligation is incurred.

This Operator's Manual should be considered a permanent part of the snowmobile and must remain with the snowmobile at the time of resale. If the snowmobile changes ownership more than once, contact Arctic Cat Inc., Service Department, P.O. Box 810, Thief River Falls, MN 56701, for proper registration information. This manual was prepared by the Product Service and Warranty Department of Arctic Cat Inc.

Every Arctic Cat Snowmobile meets or exceeds the standards of the Snowmobile Safety and Certification Committee and displays the SSCC decal. Arctic Cat Inc. endorses and encourages the safe use of all snowmobiles. Always wear a helmet and eye protection. Drive with caution, observe all state and local regulations, and respect the rights of others. ISMA members like Arctic Cat do their part to improve trails, sponsor events, and generally support the sport of snowmobiling. As a member of the National Snowmobile Foundation, Arctic Cat Inc. promotes snowmobiling through education, charity, and research programs.

© 2011 Arctic Cat Inc.

Printed in U.S.A.



## Declaration of Conformity

Application of council directives: EMC Directive 2004/108/EC  
 Issued by European Commission. EC Machinery Directive 2006/42/EC

Type of Equipment: Snowmobile  
 Brand Name: Arctic Cat  
 Model Numbers:


S2012F1NANUSB	S2012F8HEPUSG	S2012M1NNAUSB	S2012XFHSPUSO
S2012F1NELUSW	S2012F8HEPUSO	S2012M1NSPUSG	S2012XFNANUSB
S2012F1NEPUSG	S2012F8HLEUSW	S2012M1NSPUSO	S2012XFNLEUSW
S2012F1NEPUSO	S2012F8HLXUSB	S2012M8H3EUSB	S2012XFNLEUSW
S2012F1NLEUSW	S2012F8HLXUSG	S2012M8HHCUSW	S2012XFNLXUSB
S2012F1NLXUSB	S2012M1N3EUSB	S2012M8HSEUSG	S2012XFNLXUSG
S2012F1NLXUSG	S2012M1NANUSB	S2012M8HSEUSO	S2012XFNNAUSB
S2012F1NNAUSB	S2012M1NE3USB	S2012M8HSPUSG	S2012XFNTPUSB
S2012F1NTPUSG	S2012M1NE4USG	S2012M8HSPUSO	S2012XFNTPUSG
S2012F1NTPUSO	S2012M1NE4USO	S2012XFHLXUSB	S2012XFNTPUSO
S2012F1NTSUSB	S2012M1NELUSW	S2012XFHLXUSG	S2012XFNTSUSB
S2012F1NTSUSG	S2012M1NHCUSW	S2012XFHSPUSB	S2012XFNTSUSG
S2012F8HANUSB	S2012M1NLEUSW	S2012XFHSPUSG	

Standards to which conformity is declared:

EMC: EN 55012, EN 61000-6-2  
 MACHINERY: EN 12100:2010

Manufacturer (if not issuing agent): Arctic Cat Inc.  
 601 Brooks Ave. S.  
 Thief River Falls, MN  
 56701 USA

I, the undersigned, hereby declare that the equipment specified above conforms to the directive(s) and standard(s) as specified.



Brad Darling  
 Vice President/General Manager - Snowmobile Division



## SNOWMOBILE SAFETY RULES

Arctic Cat® endossa et encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.

### RÈGLEMENTS DE SÉCURITÉ EN MOTONEIGE

Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Respectez toujours ces règlements qui vous permettront de profiter de votre plaisir. Respectez toujours ces règlements qui vous permettront de profiter de votre plaisir. Veuillez vous référer au manuel du réparateur pour les instructions complètes de sécurité. Veuillez vous référer au manuel du réparateur pour les instructions complètes de sécurité.

### SAKERHETSREGLER VID SNÖSKOTERKÖRNING

Arctic Cat® önskar till fröjdhälsan att användarna av sina produkter ska följa dessa regler när de är ute och kör. Arctic Cat® önskar till fröjdhälsan att användarna av sina produkter ska följa dessa regler när de är ute och kör.

### MOOTTORIKELKAN TURVASÄÄNNÖT

Arctic Cat® korostaa ja kannustaa moottorikelkkojen turvaseisäkäyttöä. Arctic Cat® korostaa ja kannustaa moottorikelkkojen turvaseisäkäyttöä. Näitä sääntöjä tarkkaan noudattamalla saat kokea moottorikelkan ilon ja hyödyn. Näitä sääntöjä tarkkaan noudattamalla saat kokea moottorikelkan ilon ja hyödyn.

### SIKERHETSREGLER FOR BRUK AV SNØSCOOTER

Arctic Cat® oppfordrer brukerne av sine produkter til å følge disse reglene når de er ute og kjører. Arctic Cat® oppfordrer brukerne av sine produkter til å følge disse reglene når de er ute og kjører.

### NORME DI SICUREZZA PER LE MOTOSLITTE

Le Arctic Cat® esortano gli Incaresaggi a seguire le seguenti norme. Le Arctic Cat® esortano gli Incaresaggi a seguire le seguenti norme.

### スノーモービルの安全運転ルール

Arctic Cat® は、ユーザーが安全にスノーモービルを楽しむことを目的として、以下の安全運転ルールを定めています。 Arctic Cat® は、ユーザーが安全にスノーモービルを楽しむことを目的として、以下の安全運転ルールを定めています。

<p><b>1</b> Don't drink and ride. <b>飲酒運転はしないこと。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>	<p><b>2</b> Always wear a helmet. <b>常時、ヘルメットを着用すること。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>
<p><b>3</b> Watch out for thin ice/water. <b>氷水や氷が薄く凍っている場所には注意すること。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>	<p><b>4</b> Use caution when crossing road/train tracks. <b>道路や線路を横切る際には注意すること。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>

## Snowmobile Safety Rules


<p><b>5</b> Don't ride after midnight. <b>真夜中以後は乗らないこと。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>	<p><b>6</b> Beware of trees and other hazards. <b>木や障害物に用心すること。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>
<p><b>7</b> Always use a solid knob for towing. <b>牽引にはしつかりロープを使うこと。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>	<p><b>8</b> Observe proper rider capacity. <b>乗客数を厳守すること。二人乗りは一人を乗せ、二人乗りは二人を乗せ。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>
<p><b>9</b> Check controls and maintain your machine. <b>操縦系のメンテナンスの要をすること。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>	<p><b>10</b> Be of legal age. <b>運転資格のある年齢に達すること。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>
<p><b>11</b> Read and understand your Operator's Manual. <b>オーナーズマニュアルをよく読み、守ること。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>	<p><b>12</b> Obey all local laws and regulations and use caution. <b>地域の法律や規制を守り、安全を第一に行動すること。</b></p> <p>Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Arctic Cat® encourage les utilisateurs de ses produits de respecter les règles de sécurité. Always follow these rules to ensure your continued enjoyment of this sport. Always follow these rules to ensure your continued enjoyment of this sport.</p>



## General Information

### Snowmobile Identification

The Arctic Cat Snowmobile has two important identification numbers. The Vehicle Identification Number (VIN) is stamped into the tunnel near the right-side footrest and on a decal beneath the seat. The decal also displays pertinent production information. The Engine Serial Number (ESN) is stamped into the crankcase of the engine.



0726-383


These numbers are required by the dealer to complete warranty claims properly. No warranty will be allowed by Arctic Cat Inc. if the engine serial number or VIN is removed or mutilated in any way.

Always provide the snowmobile name, VIN, and ESN when contacting an authorized Arctic Cat Snowmobile dealer for parts, service, accessories, or warranty. If the complete engine must be replaced, ask the dealer to notify Arctic Cat for correct registration information.

### Control Locations


Shown are the typical control locations for Arctic Cat snowmobiles. Location of a specific control will vary according to model.

#### XF 800/XF 1100/M 800/M 1100 Models



0745-832

#### F 800/F 1100 Models



0745-842



## Gasoline-Oil

### Recommended Gasoline (1100 cc Models)

The recommended gasoline to use in these snowmobiles is 87 octane regular unleaded. In many areas, oxygenates (either ethanol or MTBE) are added to the gasoline. Oxygenated gasolines containing up to 10% ethanol are acceptable gasolines.

■ **NOTE:** The turbo models will detect lower octane gasoline and reduced engine performance will result. It is recommended that 91 octane (minimum) gasoline be used in these models.

When using ethanol blended gasoline, it is not necessary to add a gasoline antifreeze since ethanol will prevent the accumulation of moisture in the fuel system.

#### CAUTION

Do not use white gas or gasolines containing methanol. Only Arctic Cat approved gasoline additives should be used.

### Recommended Gasoline (800 cc Models)

The only recommended gasoline to use in these snowmobiles is 91 octane (minimum).

■ **NOTE:** For optimum performance, use only 91 octane (minimum) gasoline.

#### CAUTION

If a situation arises wherein 91 octane gasoline is not available, 87 octane gasoline can be substituted; however, do not prolong the usage of 87 octane gasoline as it will cause poor engine performance.

In many areas, oxygenates (either ethanol or MTBE) are added to the gasoline. Oxygenated gasolines containing up to 10% ethanol are acceptable gasoline. Do not use gasolines containing methanol.

#### CAUTION

Do not use white gas or gasolines containing methanol. Only Arctic Cat approved gasoline additives should be used.

### Recommended Injection Oil (800 cc Models)

The recommended oil to use in the oil-injection system is either Arctic Cat APV Synthetic 2-Cycle Oil (p/n 4639-349 - qt) or (p/n 5639-469 - gal.) or Formula SS Semi-Synthetic Oil (p/n 5639-470 - qt) or (p/n 5639-471 - gal.). These oils are specially formulated to be used either as an injection oil or as a pre-mix oil (for break-in) and meets all of the lubrication requirements of the Arctic Cat snowmobile engine.

#### CAUTION

Any oil used in place of the recommended oil could cause serious engine damage.

### Recommended Engine Oil (1100 cc Models)

The recommended oil to use is Synthetic 0W-40 Oil (p/n 5639-172 - qt) or (p/n 5639-173 - gal.).

After the engine break-in period, the engine oil should be changed every 2500-3000 miles on the non-turbo models or 1500-2000 miles on the turbo models and before prolonged storage.

### Filling Gas Tank

Since gasoline expands as its temperature increases, the gas tank must be filled to its rated capacity only. Expansion room must be maintained in the tank particularly if the tank is filled with cold gasoline and then moved to a warm area.

Also, if the snowmobile is to remain on a trailer after filling the gas tank, the bed of the trailer must be maintained level to prevent gasoline from draining out through the gas tank vent hose.

#### ⚠ WARNING

Always fill the gas tank in a well-ventilated area. Never add gasoline to the snowmobile gas tank near any open flames or with the engine running. DO NOT SMOKE while filling the gas tank. Do not sit on the snowmobile without first installing the gas tank cap.



### Break-In Gas/Oil Mixing Instructions (800 cc Models)

Before mixing gasoline and oil, make sure the oil is at room temperature (20° C/68° F). Use a U.L. approved 22.7 l (6 U.S. gal.) gasoline container for mixing the gasoline and oil. To properly mix the fuel at a 100:1 ratio, use the following procedure:

#### CAUTION

**Never mix oil and gasoline in the snowmobile gas tank.**

1. Pour gasoline into the gasoline container until approximately half full.
2. Pour 236 ml (8 fl oz) of the recommended 2-cycle oil into the gasoline container.
3. Install cap on gasoline container and shake the mixture vigorously.
4. Fill the gasoline container with gasoline; then cap the gasoline container and shake the mixture vigorously.
5. Using a fine-mesh screened funnel, pour the fuel mixture from the gasoline container into the snowmobile gas tank.

#### WARNING

**Always fill the gas tank in a well-ventilated area. Never add gasoline to the snowmobile gas tank near any open flames or with the engine running. DO NOT SMOKE while mixing fuel or filling the gas tank.**

### Engine Break-In

The Arctic Cat engine (when new or rebuilt) requires a short break-in period before the engine is subjected to heavy load conditions.

#### 800 cc Models

Arctic Cat requires that the first tankful of fuel be premixed at a 100:1 ratio in all oil-injection models.

During the break-in period, a maximum of 1/2 throttle is recommended; however, brief full-throttle accelerations and variations in driving speeds contribute to good engine break-in. After one (1) tankful break-in period, the snowmobile may be taken to an authorized Arctic Cat Snowmobile dealer for a checkup. This checkup is at the discretion and the expense of the snowmobile owner.

#### CAUTION

**DO NOT exceed the one (1) tankful limitation of a 100:1 gas/oil break-in mixture. Continuous use of a gas/oil mixture could cause spark plug fouling and excessive carbon buildup.**

#### 1100 cc Models

This engine does not require any premixed fuel during the break-in period.

#### CAUTION

**DO NOT use premixed fuel in the snowmobile gas tank. Engine damage will occur.**

To ensure trouble-free operation, careful adherence to the following break-in guidelines will be beneficial.

0-200 miles	1/2 Throttle (45 MPH-max)
200-400 miles	1/2-3/4 Throttle
400-600 miles	1/2-3/4 Throttle *

\* With occasional full-throttle operation.

To ensure proper engine break-in, Arctic Cat recommends that the engine oil and filter be changed after 500 miles. This service is at the discretion and expense of the snowmobile owner.

### Drive Belt Break-In

Drive belts require a break-in period of approximately 25 miles. Drive the snowmobile for 25 miles at 3/4 throttle or less. By revving the engine up and down (but not exceeding 60 mph), the exposed cord on the side of a new belt will be worn down. This will allow the drive belt to gain its optimum flexibility and will extend drive belt life.



■ **NOTE:** Before starting the snowmobile in extremely cold temperatures, the drive belt should be removed and warmed up to room temperature. Once the drive belt is at room temperature, install the drive belt (see Drive Belt sub-section in the Maintenance section).

### CAUTION

Never run the engine with the drive belt removed. Excessive revving of the engine could result in serious engine damage and drive clutch failure.

### Cold Drive-Away Function (1100 cc Models)

On these models, there is a “cold drive-away” function incorporated within the engine.

■ **NOTE:** When cold-starting the engine, the coolant temperature warning icon will illuminate and the TEMP display on the readout screen will begin to flash. With the engine in this temperature range, the RPM “limit” of the engine will be below drive system engagement speed. As the engine warms, the coolant temperature warning icon will begin to flash, the TEMP display will continue to flash, and the RPM “limit” of the engine will increase allowing the snowmobile to move without full-throttle operation. When the engine reaches proper operating temperature, the coolant temperature warning icon and the TEMP display will go out.

### CAUTION


It is extremely important that the engine is properly warmed up before subjecting the engine to high speed operation or heavy loads. The engine should be allowed to idle at least 3-4 minutes before it is operated at more than 1/2 throttle. In extremely cold conditions, the warm-up time will be longer. Cold seizure and piston scuffing caused by insufficient warm-up will not be covered by warranty. Also, do not idle the engine for excessively long periods of time.

### Speedometer/Tachometer

These snowmobiles are equipped with different speedometer/tachometer styles. Determine which style your model is equipped with and use the appropriate following information.

### Indicator Icons (Standard Gauge)

Certain models are equipped with a standard gauge combination speedometer/tachometer. Indicator icons are incorporated within the speedometer/tachometer. Also incorporated into the speedometer/tachometer is a digital readout screen.



- A. Oil Pressure/Low Oil
- B. Coolant Temperature
- C. Low Fuel
- D. Fuel Level
- E. Service
- F. High Beam
- G. Charging System (1100 cc Models)

### RPM/MPH (kph)

By pushing the left button once, the RPM and MPH will be displayed (one on the readout screen and one with the needle). By pushing the button once again, the functions will be reversed.

By pushing the left button (with speed being displayed) for more than two seconds, the display will change between standard mph or metric kph. Release the button when desired display appears.



With RPM displayed on the readout screen by pushing and holding the left button, maximum RPM will be displayed on the readout screen. The maximum RPM readout will reset when the right button is pushed (while maximum RPM is displayed).

### **Odometer/Trip-Meter (1)/ Trip-Meter (2)/Hour- Meter/Clock**

■ **NOTE:** The clock is available on electric start models only.

By pushing the right button, the readout screen will display odometer, trip-meter (1), trip-meter (2), hour-meter, and clock. To reset the trip meter with the trip meter displayed, push and hold the right button until the display is cleared. The hour-meter readout will not reset.

### **Clock (Electric Start)**

With the clock selected on the readout screen by pushing and holding the right button for two seconds, the option of selecting the 12-hour or 24-hour clock is available. Push the left button for 12-hour display; push the right button for 24-hour display. At this point, the hours and minutes will begin to flash. Push the left button to change the hour display; push the right button to change the minute display (either tap the buttons for individual number display or push and hold the buttons for rapid number display).

■ **NOTE:** During clock setting if neither button (left, right) is pushed within a 5-second time period, the clock-setting mode will be exited with changes saved.

### **Service Icon**

On electric start models, the icon should illuminate each time the key is turned to RUN or START, and it should go out when the engine starts. If the icon stays illuminated (on electric start models) or it illuminates while the engine is running, the system is receiving input that is outside of its established parameters. If the icon illuminates indicating an error, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

### **Coolant Temperature Warning Icon**

■ **NOTE:** On the 1100 cc models when cold-starting the engine, the coolant temperature warning icon will illuminate, the readout screen will display TEMP, and engine RPM limit will be below drive system engagement speed.

When the engine reaches proper operating temperature, the coolant temperature warning icon and TEMP display will cease to flash.

If the coolant temperature rises too far above proper operating temperature, the coolant temperature warning icon will flash a warning (alert) and the engine will “surge” to alert the operator. If the coolant temperature rises to a critical point above proper operating temperature, the coolant temperature warning icon will cease flashing and will remain constantly illuminated.

■ **NOTE:** If the coolant temperature icon is constantly on, the engine will shut off if vehicle speed is reduced to 1.5 kph (0.9 MPH) or slower.

### **CAUTION**

At this point, take precautionary measures such as changing to loose snow terrain, shutting the engine off (allowing the engine to cool down), and checking coolant level. If unable to either determine or remedy the problem, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

### **Charging System Warning Icon (1100 cc Models)**

The Charging System Warning Icon is designed to warn the operator if the battery charging system is not functioning. The icon should illuminate each time the key is turned to RUN or START, and it should go out when the engine starts. If the icon stays illuminated or it illuminates while the engine is running, the battery is not being charged, and the snowmobile is running on battery reserve power only.



If the Charging System Warning Icon illuminates, you should, as soon as possible, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner. The engine **WILL NOT RUN** without battery power.

### Low Oil Warning Icon (800 cc Models)

The Low Oil Warning Icon is designed to alert the snowmobile operator when the oil in the oil injection reservoir gets below a prescribed level; however, it is highly recommended that a visual verification of the oil level in the reservoir be done prior to operating the snowmobile. Once the Low Oil Warning Icon illuminates during operation of the snowmobile, the operator must periodically monitor the level of oil in the reservoir and must fill the reservoir the next time gasoline is added to the gas tank. The “alert level” of the Low Oil Warning Icon is approximately equal to 1 tankful of gasoline under normal operating conditions.


### Oil Pressure Warning Icon (1100 cc Models)

The Oil Pressure Warning Icon indicates engine oil pressure, not the oil level; however, if the oil level is low, it may affect oil pressure.

The icon should illuminate each time the ignition switch is turned to RUN or START, and it should go out when the engine starts. If the icon illuminates while the engine is running, oil pressure has been lost and the engine will automatically shut off.


If oil pressure is lost, use the following procedure to check the oil level:

1. With the engine off, note the oil level in the sight glass. If the level is below the sight glass, add only enough recommended oil until it is visible in the sight glass. **DO NOT** overfill the reservoir with oil.



0746-166

2. Open the air bleed bolt located on the oil pump (beneath the coolant tank) to purge air from the oil hose.



PC016A

■ **NOTE:** When air can no longer be heard purging from oil pump bleed, tighten the bleed bolt to 7.5 ft-lb.

### CAUTION

**Do not attempt to start the engine with the bleed bolt open.**

3. Start the engine. The warning icon should go out within five seconds.
4. If the warning icon does not go out, shut the engine off immediately and repeat step 2; then repeat step 3.

If the warning icon does not go out or if the engine does not start, take the snowmobile to an authorized Arctic Cat Snowmobile dealer. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

### Indicator Icons (Deluxe Gauge)

Certain models are equipped with a deluxe gauge combination speedometer/tachometer. Indicator icons are incorporated within the speedometer/tachometer. Also incorporated into the speedometer/tachometer is a digital read-out screen.





FZ001A

- A. High Beam
- B. Oil Pressure/Low Oil
- C. Coolant Temperature
- D. Increment Button
- E. Select Button
- F. Decrement Button
- G. Service
- H. Charging System (1100 cc Models)

### RPM/MPH (kph)

By pushing the increment button once, the RPM and MPH will be displayed (one on the readout screen and one with the needle). By pushing the button once again, the functions will be reversed.

By pushing the increment button (with speed being displayed) for more than two seconds, the display will change between standard mph or metric kph.

With RPM displayed on the readout screen by pushing and holding the increment button, maximum RPM will be displayed on the readout screen. The maximum RPM readout will reset when the decrement button is pushed (while maximum RPM is displayed).

### Odometer/Trip-Meter (1)/Trip-Meter (2)/Hour-Meter

By pushing the decrement button, the readout screen will display odometer, trip-meter (1), trip-meter (2), and hour-meter. To reset the trip meter with the trip meter displayed, push and hold the decrement button until the display is cleared. The hour-meter readout will not reset.

### Clock/Altimeter

By pushing the select button, the readout screen will display clock, altimeter, and maximum altimeter.

To set the clock, select clock on the display by pushing and holding the select button for two seconds; the option of selecting the 12-hour or 24-hour clock mode is available. Push the increment button to toggle between the 12-hour display and the 24-hour display. When desired mode is displayed, push the select button.

At this point, the hours display will begin to flash. Push the increment button to increase the hours; push the decrement button to decrease the hours. Pushing and holding a button will accelerate the number display. When desired hour number is displayed, push the select button.

At this point, the minutes display will begin to flash. Push the increment button to increase the minutes; push the decrement button to decrease the minutes. Pushing and holding a button will accelerate the number display. When desired minute number is displayed, push the select button.

■ **NOTE:** During clock setting if no button (increment, decrement, select) is pushed within a 5-second time period, the clock-setting mode will be exited with changes saved.

■ **NOTE:** The altimeter readout is based off barometric pressure and may require calibration as weather conditions change.

To set/calibrate the altimeter to an established altitude with altimeter selected on the display screen by pushing and holding the select button for a minimum of two seconds, the acronym CAL will be displayed on the readout screen for one second; then the altitude value will flash. Push the increment button to increase the displayed altitude; push the decrement button to decrease the displayed altitude. Pushing and holding a button will accelerate the number display.



■ **NOTE:** If MPH has been selected in the speed readout, the altitude value will be displayed in feet. If kph has been selected in the speed readout, the altitude value will be displayed in meters.

To reset the maximum altimeter readout with the maximum altimeter displayed, push and hold the select button for a minimum of two seconds.

### **Service Icon**

On electric start models, the icon should briefly illuminate each time the key is turned to RUN or START, and engine is started; then it should go out when the engine starts. If the icon stays illuminated (on electric start models) or it illuminates while the engine is running, the system is receiving input that is outside of its established parameters. If the icon illuminates indicating an error, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

### **Coolant Temperature Warning Icon**

■ **NOTE:** On the 1100 cc models when cold-starting the engine, the coolant temperature warning icon will illuminate, the readout screen will display TEMP, and engine RPM limit will be below drive system engagement speed.

When the engine reaches proper operating temperature, the coolant temperature warning icon and TEMP display will cease to flash.

If the coolant temperature rises too far above proper operating temperature, the coolant temperature warning icon will flash a warning (alert) and on the 1100 cc models, the engine will “surge” to alert the operator. If the coolant temperature rises to a critical point above proper operating temperature, the coolant temperature warning icon will cease flashing and will remain constantly illuminated.

■ **NOTE:** On the 1100 cc models if the coolant temperature icon is constantly on, the engine will shut off if vehicle speed is reduced to 1.5 kph (0.9 MPH) or slower.

### **CAUTION**

At this point, take precautionary measures such as changing to loose snow terrain, shutting the engine off (allowing the engine to cool down), and checking coolant level. If unable to either determine or remedy the problem, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

### **Charging System Warning Icon (1100 cc LXR Models)**

The Charging System Warning Icon is designed to warn the operator if the battery charging system is not functioning. The icon should illuminate each time the key is turned to RUN or START, and it should go out when the engine starts. If the icon stays illuminated or it illuminates while the engine is running, the battery is not being charged, and the snowmobile is running on battery reserve power only.

If the Charging System Warning Icon illuminates, you should, as soon as possible, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner. The engine **WILL NOT RUN** without battery power.

### **Low Oil Warning Icon (800 cc Models)**

The Low Oil Warning Icon is designed to alert the snowmobile operator when the oil in the oil injection reservoir gets below a prescribed level; however, it is highly recommended that a visual verification of the oil level in the reservoir be done prior to operating the snowmobile. Once the Low Oil Warning Icon illuminates during operation of the snowmobile, the operator must periodically monitor the level of oil in the reservoir and must fill the reservoir the next time gasoline is added to the gas tank. The “alert level” of the Low Oil Warning Icon is approximately equal to 1 tankful of gasoline under normal operating conditions.




## Oil Pressure Warning Icon (1100 cc LXR Models)

The Oil Pressure Warning Icon indicates engine oil pressure, not the oil level; however, if the oil level is low, it may affect oil pressure.

The icon should illuminate each time the ignition switch is turned to RUN or START, and it should go out when the engine starts. If the icon illuminates while the engine is running, oil pressure has been lost and the engine will automatically shut off.


If oil pressure is lost, use the following procedure to check the oil level:

1. With the engine off, note the oil level in the sight glass. If the level is below the sight glass, add only enough recommended oil until it is visible in the sight glass. DO NOT overfill the reservoir with oil.



0746-166

2. Open the air bleed bolt located on the oil pump (beneath the coolant tank) to purge air from the oil hose.



PC016A

■ **NOTE:** When air can no longer be heard purging from oil pump bleed, tighten the bleed bolt to 7.5 ft-lb.

## CAUTION

**Do not attempt to start the engine with the bleed bolt open.**

3. Start the engine. The warning icon should go out within five seconds.
4. If the warning icon does not go out, shut the engine off immediately and repeat step 2; then repeat step 3.

If the warning icon does not go out or if the engine does not start, take the snowmobile to an authorized Arctic Cat Snowmobile dealer. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

## Diagnostic Codes

Diagnostic codes are activated by the ECU and may be displayed on the readout screen for a number of reasons.

If a code is displayed while the engine is running, the ECU is receiving input that is outside of its established parameters. If a code has been activated, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

## 800 cc Models

Additional codes are displayed on the readout screen. Refer to the following chart for diagnostic codes.

Code	Trouble
2	Failure in injector(s).
4	Open or short circuit in barometric pressure sensor.
5	Open or short circuit in intake air temperature sensor.
6	Open or short circuit in water temperature sensor.
7	Open or short circuit in throttle position sensor.
12	Failure in ignition coil(s).
16	Incorrect adjustment/failure in APV cable.
17	Failure in exhaust temperature sensor.
18	Failure in servomotor.
21	Open or short circuit in/or loose knock sensor.
OCTN	Low octane gasoline.



## 1100 cc Models

These diagnostic codes are displayed on the readout screen incorporated within the speedometer/tachometer. Refer to the following chart for diagnostic codes.


Code	Trouble
1	Failure in the fuel system.
2	Failure in injector (PTO).
3	Failure in injector (MAG).
4	Failure in barometric pressure sensor.
5	Open or short circuit in intake manifold air temperature sensor.
6	Open or short circuit in water temperature sensor.
7	Open or short circuit in throttle position sensor.
8	Open or short circuit in manifold air pressure sensor.
9	Failure in crankshaft position sensor.
11	Failure in speed sensor.
12	Failure in coil (MAG).
13	Failure in coil (PTO).
14	Failure in ISC valve.
15	Failure in oxygen sensor.
19	Failure in camshaft position sensor.
21	Open or short circuit in/or loose knock sensor.
22*	Failure in injector (PTO secondary).
23*	Failure in injector (MAG secondary).
25	Failure in shifting system/gear position switch.
26	Malfunction in air pressure sensor.
29	Malfunction in shift control switch.
OCTN*	Low octane gasoline.

\* Turbo models

## Handlebar Height/Tilt (M 800 Sno Pro/LTD/HCR/XF 800 High Country Models)

To adjust handlebar height, use the following procedure:

1. From each side of the steering post, compress the locking tabs to unlock the handlebar.




0745-843

2. With the tabs compressed, adjust the handlebar up or down to the desired position; then release the tabs to lock the handlebar in place.

To adjust handlebar tilt, use the following procedure:

1. Loosen the four cap screws and tilt the handlebar to the desired position.



0745-845

2. Tighten the four cap screws to 15 ft-lb.

## WARNING


Tighten the cap screws according to specifications to prevent unexpected "movement" of the handlebar during operation over rough terrain. DO NOT position handlebar so steering (maximum right/left turning capabilities) or throttle and brake controls are affected.

## Handlebar Tilt

The handlebar can be adjusted to the operator's preference. To adjust the handlebar, use the following procedure:

1. Remove the handlebar cover; then loosen the eight cap screws securing the handlebar caps to the riser and the riser to the steering post.





0745-848

2. Adjust the handlebar to operator's desired position, tighten the cap screws evenly to 15 ft-lb, and check steering for maximum right/left turning capabilities.

■ **NOTE:** Do not rotate the handlebar to a position that allows air to enter the brake system.

### **⚠ WARNING**

Tighten cap screws according to specifications to prevent unexpected "movement" of the handlebar during operation over rough terrain. **DO NOT** position the handlebar so steering (maximum right/left turning capabilities) or throttle and brake controls are affected.

## **Speedometer/Tachometer Angle**

The speedometer/tachometer can be adjusted to the operator's desired position. To adjust, use the following procedure.

1. Loosen the lock nuts and cap screws on each side of the speedometer/tachometer bracket.
2. Adjust the speedometer/tachometer to the desired angle; then tighten the lock nuts securely.

## **Exhaust System**

The exhaust system is designed to reduce noise and to improve the total performance of the engine. If any exhaust system component is removed from the engine and the engine is run, severe engine damage will result.

## **Air-Intake Silencer**

Used in conjunction with the fuel intake system is a specially designed air-intake silencer. The purpose of the silencer is to quiet the intake of fresh air. Since the fuel intake system is calibrated with the air-intake silencer in place, the engine must never be run with the silencer removed. Performance will not be improved if the air-intake silencer is removed. In contrast, severe engine damage will occur.

### **CAUTION**

**These snowmobiles are not designed to be operated in dusty conditions. Operating the snowmobile in dusty conditions will result in severe engine damage.**

## **Cooling System**

These snowmobiles are equipped with a closed liquid cooling system for engine cooling. The cooling system should be inspected daily for leakage and damage. Also, the coolant level should be checked daily. If leakage or damage is detected, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

When filling the cooling system reservoir, use an ethylene glycol-based coolant/water mixture which will satisfy the coldest anticipated weather conditions of your area in accordance with the coolant manufacturer's recommendations.

■ **NOTE:** On the HCR models if operating on ice or hard-packed snow, the ice scratchers must be engaged to reduce engine overheating.

For checking/filling cooling system, refer to Coolant Level sub-section in the Maintenance section.

## **Battery (Electric Start)**

It is extremely important that the battery be maintained at full charge at all times and that the battery connections be clean and tight. If charging the battery becomes necessary, refer to Battery sub-section in the Maintenance section.



### CAUTION

On the 1100 cc models, always turn the ignition switch key to the OFF position when the snowmobile is not being used. Leaving the ignition switch in the ON position will result in discharging the battery and possible damage to the battery.

### Jump-Starting (1100 cc Models)

■ **NOTE:** Arctic Cat does not recommend jump-starting a snowmobile with a dead battery but rather to remove the battery, service it, and correctly charge it; however, in an emergency, it may be necessary to jump-start a snowmobile. If so, use the following procedure to carefully and safely complete this procedure.

### ⚠ WARNING

Improper handling or connecting of a battery may result in severe injury including acid burns, electrical burns, or blindness as a result of an explosion. Always remove rings and watches.

■ **NOTE:** To access the battery, the seat must be removed (see Removable Seat sub-section in this section).

1. On the snowmobile to be jump-started, slide any terminal boots away.

### ⚠ WARNING

Any time service is performed on a battery, the following must be observed: keep sparks, open flame, cigarettes, or any other flame away. Always wear safety glasses. Protect skin and clothing when handling a battery. When servicing a battery in an enclosed space, keep the area well-ventilated.

2. Inspect the battery for any signs of electrolyte leaks, loose terminals, or bulging sides. Leaking or bulging battery cases may indicate a frozen or shorted battery.

### ⚠ WARNING

If any of these conditions exist, DO NOT attempt to jump-start, boost, or charge the battery. An explosion could occur causing serious injury.

3. Inspect the vehicle to be used for jump-starting to determine if voltage and ground polarity are compatible. The vehicle must have a 12-volt DC, negative ground electrical system.

### CAUTION

Always make sure the electrical systems are of the same voltage and ground polarity prior to connecting jumper cables. If not, severe electrical damage may occur.

4. Move the vehicle to be used for the jump-start close enough to ensure the jumper cables easily reach; then set and lock the brakes, shut off all electrical accessories, and turn the ignition switch OFF.

■ **NOTE:** Make sure all switches on the snowmobile to be jump-started are turned OFF.


5. Disconnect all external accessories such as cell phones, GPS units, and radios on both vehicles.

### CAUTION

Failure to disconnect electronic accessories during jump-starting may cause system damage due to power spikes.

6. Attach one clamp of the positive (red) cable to the positive (+) terminal (1) of the dead battery (C) being careful not to touch any metal with the other clamp; then attach the other clamp of the positive (red) cable to the positive (+) terminal (2) of the good battery (B).





■ **NOTE:** Some jumper cables may be the same color but the clamps or ends will be color-coded red and black.

7. Attach one clamp of the negative jumper cable (black) to the negative (-) terminal (3) of the good battery (B); then attach the other clamp of the negative jumper cable (black) (4) to an unpainted metal surface (A) on the engine or frame well away from dead battery and fuel system components.

### **⚠ WARNING**

**Never make the final connection to a battery as a spark could ignite hydrogen gases causing an explosion of the battery resulting in acid burns or blindness.**

8. Stand well away from the dead battery and start the vehicle with the good battery. Allow the vehicle to run for several minutes applying some charge to the dead battery.
9. Start the snowmobile with the dead battery and allow it to run for several minutes before disconnecting the jumper cables.
10. Remove the jumper cables in opposite order of hook-up (4, 3, 2, 1). Be careful not to short cables against bare metal.

■ **NOTE:** Have the battery and electrical system checked prior to operating the snowmobile again.

## **Drive Clutch and Driven Pulley**

The drive clutch and driven pulley do not require lubrication; therefore, no special maintenance is required by the snowmobile owner except for periodical cleaning (see the Periodic Maintenance Checklist in the Maintenance section).

However, the drive clutch and driven pulley should be disassembled, cleaned, and inspected by an authorized Arctic Cat Snowmobile dealer after every 800 miles of operation or at the end of the snowmobiling season whichever occurs first. This service is at the discretion and expense of the snowmobile owner.

When operating the snowmobile at high altitudes, it may be necessary to change certain component parts of the drive clutch and/or the driven pulley. See an authorized Arctic Cat Snowmobile dealer for further information.

### **CAUTION**

**DO NOT attempt to service the drive clutch and driven pulley. The drive clutch and driven pulley must be serviced by an authorized Arctic Cat Snowmobile dealer only.**

## **Drive Clutch/Driven Pulley Alignment**

The alignment between the drive clutch and driven pulley is set at the factory. Normally, no adjustment is necessary as long as neither the drive clutch nor the driven pulley is removed or disassembled. However, if premature drive belt wear is experienced or if the drive belt turns over, the drive clutch/driven pulley alignment must be checked. Take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

## **Fuel Pump**

The fuel pump is designed to provide adequate amount of gas to the injectors at all throttle settings. If a fuel delivery problem is suspected, take the snowmobile to an authorized Arctic Cat Snowmobile dealer. If not under warranty, this service is at the discretion and expense of the snowmobile owner.



## Shock Absorbers Rebuildable Gas

Each shock absorber should be visibly checked weekly for fluid leakage, cracks or breaks in the body/reservoir, or a bent shaft. If any one of these conditions is detected, replacement or service is necessary. Take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

■ **NOTE:** When the snowmobile is operated in extremely cold weather (-23° C/-10° F or colder), a small amount of leakage may be present. Unless the leakage is excessive, replacement is not necessary.

■ **NOTE:** The frequency of servicing rebuildable shock absorbers will vary according to the types of conditions and terrain the snowmobile has been subjected to. If riding quality deteriorates (or seems to be deteriorating), take the snowmobile to an authorized Arctic Cat Snowmobile dealer for shock absorber evaluation and/or servicing. This service is at the discretion and expense of the snowmobile owner.

Servicing rebuildable shock absorbers is considered normal maintenance and is the responsibility of the owner. Take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner. Kits are available to either stiffen or soften gas shock valving. If changes in shock valving are desired, see an authorized Arctic Cat Snowmobile dealer. This service is at the discretion and expense of the snowmobile owner.

## Standard Track (XF/F Models)

Accelerated wear strip and track clip wear caused by operating on ice or hard-packed snow conditions is NOT covered under Arctic Cat Inc. warranty policy.

## Paddle Track (XF High Country/M Models)

These models are equipped with a Power Claw style track which is specially designed for use in powder snow riding conditions. When the Power Claw track is operated in hard-packed snow conditions, it will run slightly slower than a standard track and it will accelerate wear strip wear. To decrease the amount of wear strip wear, slower speeds must be maintained when operating on hard-packed trails. Accelerated wear strip wear caused by operating a Power Claw track on hard-packed snow conditions is NOT covered under Arctic Cat Inc. warranty policy.

■ **NOTE:** If operating on ice or hard-packed snow conditions, it is recommended that Ice Scratchers (p/n 5639-897) be installed to reduce wear strip wear and engine overheating.

## Track Studs (XF/F Models)

■ **NOTE:** Stud or hooker plate installation will void track and tunnel warranty.

■ **NOTE:** Stud installation can be performed by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

### **WARNING**

When installing studs on a single-ply track, it is important to use Arctic Cat-approved studs (proper head diameter). If approved studs (proper head diameter) are not used, studs could tear free of the track causing possible injury or even death. Consult an authorized Arctic Cat Snowmobile dealer for information.

### **CAUTION**

To prevent tunnel damage from the studs, Tunnel Protector Kit (p/n 5639-752) for the XF models or (p/n 5639-668) for the F models must be installed.

For proper installation, use the following procedure:



1. Using the appropriate stud template (see chart), mark the desired stud pattern to be used.

Stud Template Chart	
Track Length	p/n
128 in.	4639-443
141 in.	4639-991

2. Using the proper-sized stud hole drill bit, drill out the stud holes.
3. Push the stud through the hole from inside the track; then place the domed support plate and lock nut on the exposed stud.
4. Using a wrench to secure the stud, tighten the lock nut on the exposed stud.

It is also recommended that whenever studs are installed on a track, carbide wear bars should be installed on the skis. Carbide wear bars complement the track studs to balance steering control under these conditions. The length of the carbide on the wear bars should be proportionate to the number of track studs (i.e. small number of track studs — short length of carbide...many track studs — long length of carbide). The proper proportion between the number of studs and carbide length on the wear bar will maintain steering balance.

### **⚠ WARNING**

Always balance the snowmobile with the proper proportion between the number of studs and carbide length on the wear bars. Do not “over drive” conditions; use common sense in all operating conditions.

### **CAUTION**

Do not use studs that are more than 9.525 mm (0.375 in.) longer than the track lug height.

### **⚠ WARNING**

Do not operate a snowmobile with loose studs as they may be thrown from the track. Always use a shielded safety stand whenever performing any maintenance or adjustments.


### **⚠ WARNING**

**DO NOT stand behind the snowmobile or near the rotating track. NEVER run the track at high speed when the track is suspended.**

### **Reverse Operation**

The engine reverse function offers the operator the convenience of being able to back up the snowmobile rather than having to turn the snowmobile around by hand. This feature, under most situations, should not be used to free a stuck snowmobile as it will tend to dig the skis deeper into the snow. Always use minimal speed when operating in reverse and come to a complete stop before shifting from either forward to reverse or reverse to forward.

### **Shifting Into Reverse (800 cc Models)**



741-438A

■ **NOTE:** Correct drive belt tension (deflection) is important for the reverse function to operate properly. If the belt is too tight, difficulty in engaging reverse will be experienced (the reverse function will make up to three attempts to engage into reverse, and if the function is not completed after the third attempt, the engine will shut down).

1. Always warm up the engine for 2-3 minutes prior to shifting into reverse. The reverse function is cancelled when engine temperature is below or above normal operating range.
2. Shift only with the engine at idle RPM and the snowmobile completely stopped. The reverse function will not engage if engine speed is above 3000 RPM.



3. If attempting to shift into reverse at too high engine RPM (above 3000 RPM), the reverse function will be cancelled and the coolant temperature warning icon will flash. This indicates the reverse switch button was pressed at too high RPM. The operator must reduce engine RPM below 3000 and press the button a second time.
4. Upon pressing the reverse switch button, the reverse function will make up to three attempts to engage into reverse. If the function is not completed after the third attempt, the engine will shut down.

### CAUTION

**Never shift into reverse while the snowmobile is moving forward as it is hard on the driven pulley torque bracket and the cam rollers.**

### Operating in Reverse (800 cc Models)

### CAUTION

**Never pull the recoil starter rope when the engine is running or when operating in reverse. Damage to the engine and/or recoil start system will occur.**

1. When reverse is engaged, a reverse icon will illuminate in the speedometer/tachometer and a reverse alarm will sound.
2. If the throttle lever is compressed before complete reverse engagement, the engine may shut down. Always wait for the reverse icon to illuminate and the reverse alarm to sound before backing up.
3. The system will not shift until the button is released. Also, the reverse function will cancel if operated in reverse longer than 45 seconds. Whenever the reverse function has been cancelled, the engine must be run in the forward mode for a minimum of 60 seconds at 2000 RPM before the reverse function can be used again.

### ⚠ WARNING

**Do not use high speed when backing up. Control could be lost and injury could occur.**

### CAUTION

**Do not use high speed when backing up. Damage to the drive belt and driven pulley components may occur.**

■ **NOTE:** While operating in reverse, a “rev-limiter” will activate at 6500 RPM.

4. To shift into forward, stop the snowmobile and allow the engine to idle (under 3000 RPM); then press the reverse button and release. The forward selection will be complete.
5. After shifting from reverse to forward (or from forward to reverse), apply the throttle slowly and evenly to allow the driven pulley to engage properly.
6. The reverse function is cancelled whenever the engine is shut off.


### CAUTION

**After reversing in deep powder snow conditions, make sure the snowflap does not become “caught up” in the track. Track and/or snowflap damage may occur.**

### CAUTION

**If the snowmobile is equipped with ice scratchers, the scratchers must be disengaged or component damage will occur.**

### Shifting Into Reverse (1100 cc Models)



741-438A



1. Always warm up the engine for 2-3 minutes prior to shifting into reverse.
2. With the engine at idle (under 2500 RPM) and the snowmobile at a complete stop, press the reverse switch button; then release the button. The reverse selection will be complete.

■ **NOTE:** The snowmobile must be at a complete stop and the engine running under 2500 RPM before the system will allow shifting.

■ **NOTE:** The system will not shift until the button is released.

3. When reverse is engaged, a reverse icon will illuminate in the speedometer/tachometer and a reverse alarm will sound.

### CAUTION

Never shift into reverse while the snowmobile is moving forward as it is hard on the driven pulley torque bracket and the cam rollers.

4. To shift into forward, stop the snowmobile and allow the engine to idle (under 2500 RPM); then press the reverse button and release. The forward selection will be complete.

## Operating in Reverse (1100 cc Models)

### ⚠ WARNING

Use caution and minimal speed when operating the snowmobile in reverse. Be sure the button is in the desired position.

### CAUTION

Never engage the electric starter when the engine is running or when operating in reverse. Damage to the engine and/or the electric start system will occur.

1. When shifting into reverse, always wait for the reverse icon to illuminate and the reverse alarm to sound before backing up.

■ **NOTE:** The reverse function is cancelled whenever the engine is shut off.

2. After shifting from reverse to forward (or from forward to reverse), apply the throttle slowly and evenly to allow the driven pulley to engage properly.

### CAUTION




After reversing in deep powder snow conditions, make sure the snowflap does not become "caught up" in the track. Track and/or snowflap damage may occur.

### CAUTION

If the snowmobile is equipped with ice scratchers, the scratchers must be disengaged or component damage will occur.

## Access Panel/Hood (Removing/Installing)

To remove the access panel and hood, use the following procedure:





1. Remove the hairpin clip from the pin located at the front of the access panel. Move the panel up and off the pin; then swing the panel all the way out and unhinge the panel from the lower console.
2. Remove the two torx-head screws securing the hood (located on the underside of the hood above the rear tube of the upper A-arm); then remove the two torx-head screws from the top-side of the hood securing the hood to the upper console.

■ **NOTE:** On the turbo models, remove the two torx-head screws from under the nosepiece of the hood.

3. Locate the hood harness connector (located in front of the speedometer) and unplug the connector; then move the hood slightly forward and remove the hood.

■ **NOTE:** On the turbo models, first unhook the rubber straps securing the air filter housing to the intake plenum of the hood; then move the hood slightly forward and remove the hood.

To install the access panel and hood, use the following procedure:

1. Position the hood onto the snowmobile and connect the hood harness connector.

■ **NOTE:** On the turbo models prior to securing the hood, make sure the rubber straps of the air filter housing are accessible.

2. Secure the hood with the six torx-head screws and tighten securely.

■ **NOTE:** Before installing the hood, make sure the mounting screw clips are in position.

■ **NOTE:** On the 1100 cc non-turbo models, make sure the foam seal is in place on the air intake.

■ **NOTE:** On the turbo models, make sure the air filter housing is properly connected and secured with the rubber straps to the intake plenum of the hood and turbocharger.

3. Install the access panel onto the lower console; then close the access panel and secure with the hairpin clip.


## Removable Seat

These snowmobiles are equipped with a removable seat. To remove the seat, use the following procedure:

Remove the torx-head screw from the underside of the seat; then lift on the back of the seat and move it up and rearward to remove it from the tunnel.

### CAUTION

On the 1100 cc LXR models prior to removing the seat, lift the rear of the seat and disconnect the seat heater harness connector.



746-088A

To install the seat, use the following procedure:

Slide the front of the seat into the locking position of the seat support bracket; then lower the rear of the seat into position on the tunnel. Secure with the torx-head screw.

■ **NOTE:** On the 1100 cc LXR models prior to lowering and securing the seat, connect the seat heater harness connector.

## Towing

If the snowmobile is to be towed by another snowmobile, do not tow using the loops in the skis. The tow rope should be attached to the spindles.



## Arctic Power Valve (APV) System (800 cc Models)


### CAUTION

The recommended engine oil to use is either Arctic Cat APV Synthetic 2-Cycle Oil or Formula SS Semi-Synthetic Oil (see Gasoline-Oil - Recommended Injection Oil sub-section in this section). Any substitute may cause an APV malfunction.

This RPM controlled servomotor (servo) actuated system adjusts the size of the exhaust ports to provide peak performance throughout the RPM range.


The system consists of an exhaust valve assembly mounted to the exhaust side of each cylinder and connected by adjustable cables to an electronic servo mounted beneath the hood.

■ **NOTE:** The mounting location of the servo will vary from model to model.




739-152F

At low RPM, the exhaust valves are held in the DOWN position by return springs. This gives the engine a “low port” exhaust design calibrated to provide maximum low RPM power and improve fuel economy at trail speeds.



739-152G

At high RPM, the exhaust valves are raised. This creates a “high port” exhaust design calibrated to provide maximum performance at high RPM.



739-152H

■ **NOTE:** The RPM ranges will vary from model to model.

■ **NOTE:** If the servomotor cycles three times and then shuts down, the exhaust valve cables are not adjusted correctly. The exhaust valves may also be sticking.


■ **NOTE:** APV cleaning may be done by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

## Exhaust Controlled Timing (ECT) System (800 cc Models)

This system automatically adjusts the ignition timing to provide maximum performance through a variety of operating conditions. The ECU receives input on engine RPM (demand) and exhaust pipe temperature (engine condition) and adjusts the ignition timing accordingly. This system is not adjustable and is maintenance free.

If a system fault is suspected, use an ohmmeter to check continuity of the exhaust pipe temperature sensor located in the expansion chamber. A reading of either 0 ohm or infinity indicates a failed sensor.





0737-314

■ **NOTE:** A disabled ECT system **WILL NOT** cause engine damage; however, a failed ECT system will have slower throttle response and may produce slightly less top-end performance.




## Operating Instructions

### Starting and Stopping Engine


It is imperative that the brake system be checked for wear and proper operation and that all safety checks found in the accompanying Snowmobile Safety Handbook be performed before attempting to start the engine. After the engine has been started, check the headlights (high and low beam), taillight, and brakelight to be sure they are working properly and adjusted correctly. Make sure all lights are clean to provide maximum illumination. The headlight and taillight must be clean and must be illuminated whenever the engine is running.

1. Test the operation of the brake system by compressing the brake lever. The brake lever must feel firm when compressed; then while holding the brake lever in the compressed position, measure the distance between the brake lever and the handlebar. The distance must be greater than 2.54 cm (1 in.).



0745-816

2. With the brake fluid reservoir in a level position and the cover removed, check the fluid level. The brake fluid level must be at the high brake fluid mark in the reservoir.



0745-817

3. If the brake fluid is below the high brake fluid mark, add Arctic Cat approved DOT 4 brake fluid until the fluid is at the recommended level. Install and secure the reservoir cover. Do not allow moisture to contaminate the brake system.

#### CAUTION

**Brake fluid is highly corrosive. Do not spill brake fluid on any surface of the snowmobile.**

#### WARNING

**Do not overfill the brake fluid reservoir. Overfilling the reservoir may cause the brake system to hydraulically lock. Use only Arctic Cat approved brake fluid.**

#### WARNING

**Do not start the engine if the brake system is not functioning properly. Service the brake system or have it properly repaired prior to operating the snowmobile. Serious personal injury or even death may occur if the brake system is not operating properly.**

4. Test the throttle control lever by completely compressing and releasing it several times. The lever MUST return to the idle position quickly and completely.

#### CAUTION

**Always check the coolant level before starting the engine.**

5. Move the emergency stop switch to the UP or RUN position.
6. Insert key into ignition switch; then rotate key to the RUN position.

■ **NOTE:** On the 800 cc models when a cold engine is being started, **DO NOT COMPRESS THE THROTTLE CONTROL LEVER.** If the throttle control lever is compressed, the engine will not start because the fuel/air mixture will be too lean.



7. On models with manual start, pull the recoil handle slowly until resistance is felt; then give a short quick pull. Repeat until the engine starts.

■ **NOTE:** In extremely cold weather, pull the recoil handle slowly two to three times to begin the starting procedure.

#### CAUTION

To avoid damaging the recoil starter, **DO NOT** pull the recoil rope to its limit or release the recoil handle from an extended position. Allow the rope to rewind slowly.

■ **NOTE:** On electric start models, rotate the key to the **START** position; then when the engine starts, release the key.

#### CAUTION

Do not continuously run the starter for more than 5 seconds at a time.

■ **NOTE:** When the engine starts, allow it to warm up properly. Idle the engine several minutes until the engine has reached normal operating temperature. Do not idle the engine for excessively long periods of time.

8. On the 1100 cc models, there is a “cold drive-away” function incorporated within the engine. This function is active until the engine reaches operating temperature (see Cold Drive-Away Function sub-section in the General Information section).

#### CAUTION

On the 800 cc models, it is extremely important that the engine is properly warmed up before subjecting the engine to high speed operation or heavy loads. The engine should be allowed to idle at least 3-4 minutes before it is operated at more than 1/2 throttle. In extremely cold conditions, the warm-up time will be longer. Cold seizure and piston scuffing caused by insufficient warm-up will not be covered by warranty. Also, do not idle the engine for excessively long periods of time.

9. Flooding — If the engine does not start but seems ready to start, engage the brake lever lock; then compress the throttle control lever fully and try to start the engine. When the engine starts, release the throttle control lever immediately. After the warm-up, release the brake lever lock.

■ **NOTE:** On the 800 cc models if the engine fails to start during the attempt with the throttle control lever compressed, remove the spark plugs and clean and dry them thoroughly or install a new set of properly gapped, recommended spark plugs.

10. To shut off the engine, turn the ignition key to the **OFF** position or push the emergency stop switch to the **DOWN** position.

#### CAUTION

On the 1100 cc models, always turn the ignition switch key to the **OFF** position when the snowmobile is not being used. Leaving the ignition switch in the **ON** position will result in discharging the battery and possible damage to the battery.

### Braking

The following items are items that the operator must be familiar with when operating this snowmobile and its hydraulic brake system. Important additional information on the proper maintenance of the brake system is found in the Maintenance section.

1. Use the brakes wisely. Each time the brakes are applied in all hydraulic brake systems (including automotive applications), heat is transferred to the brake fluid. The amount of heat transferred during high speed stops and/or repetitive use may be high enough to boil the brake fluid and cause the brakes to either fade or may cause an unexpected loss of brakes.



If this occurs, the brake fluid requires a cool-down period before the brakes will again function properly. This cool-down period will vary depending upon the ambient air temperature and the temperature of the brake fluid. If loss of brakes has occurred because of high fluid temperatures, do not operate the snowmobile until the cool-down period has expired and brake lever firmness has returned.

### **WARNING**

**Excessive, repetitive use of the hydraulic brake for high speed stops will cause overheating of the brake fluid and premature brake pad wear which will result in an unexpected loss of brakes.**

2. Be sure to maintain the brake fluid at the proper level and take care not to get any moisture in the system as moisture in the brake fluid lowers the boiling point. If the brake fluid is ever boiled (by high speed stops or repetitive use) or if moisture is allowed to enter the system, it must be changed. Never substitute or mix different types or grades of brake fluid.

### **WARNING**

**Use only Arctic Cat approved DOT 4 brake fluid. Never substitute or mix different types or grades of brake fluid. Brake loss can result. Check brake fluid level and pad wear before each use. Brake loss can result in severe injury or even death.**

3. Never ride the brake. Even maintaining minimal pressure on the brake lever will cause the brake pads to drag on the disc and may overheat the brake fluid.
4. The brake lever lock is not a parking brake and should not be applied for periods exceeding 5 minutes. **NEVER OPERATE THE SNOWMOBILE WITH THE BRAKE LEVER LOCK ENGAGED.**

### **WARNING**

**The brake lever lock is not a parking brake and should not be applied for periods exceeding 5 minutes. The brake lever lock maintains the brake lever in the compressed position and maintains pressure against the brake disc; however, after a period of time, the pressure applied to the brake disc may relax below the amount required to hold the snowmobile stationary.**

5. Pumping the brake lever is permissible; however, if pumping the brake lever more than twice is necessary to obtain the necessary stopping power, immediately take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.
6. When new brake pads are installed, a “burnishing” process is required (see Brake System in the Maintenance section of this manual).

## **Emergency Stopping**

There are several methods of stopping or slowing the snowmobile under a variety of situations. Identified in the following chart are the ways a snowmobile may be brought to a stop and the effectiveness under normal conditions.

Item	Function	Condition
Emergency Stop Switch	interrupts ignition circuit	ALL
Throttle/Ignition Monitor Switch	interrupts ignition circuit	ALL
Ignition Switch	interrupts ignition circuit	ALL
Brake	slows the drive system	ALL

## **Throttle/Ignition Monitor Switch**

The throttle control is equipped with a monitor switch for safety purposes which will stop the engine when a loss of return spring force occurs. If ice forms in the throttle system or if there is some other malfunction of the throttle system resulting in a loss of return spring force, the monitor switch will stop the engine when the throttle control lever is released.



### **WARNING**

If any malfunction of the throttle system occurs (such as freezing in fluffy snow) and the monitor switch does not shut off the engine, press down on the emergency stop switch **IMMEDIATELY** to stop the engine. **DO NOT** start the engine until the malfunction in the throttle system has been located and corrected.

If the snowmobile engine stops abruptly when the throttle control lever is released and the activation of the monitor switch is suspected, use the following procedure:

1. Rotate the ignition key to the OFF position.
2. Remove ice and snow from the throttle system and wait 5-10 minutes for the engine heat to thaw ice from the throttle system.
3. Test the throttle control lever by compressing and releasing it several times. The lever **MUST** return to the idle position quickly and completely.

■ **NOTE:** If the throttle control lever operates properly and the engine does not start, compress the throttle lever slightly (approximately 1/8 throttle) and try starting the engine. If the engine now starts and stops when the throttle lever is released, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

### **WARNING**

If the throttle control lever does not work properly, **DO NOT ATTEMPT TO START THE ENGINE.**

4. If the throttle control lever operates properly, rotate the ignition key to the RUN position and go through normal starting procedures.

■ **NOTE:** If the throttle control lever operates properly and the engine does not start, a malfunctioning monitor switch may be the problem. Take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner. However, if a dire emergency exists wherein the engine must be started, disconnect the throttle monitor switch located in the right-side handlebar control.

■ **NOTE:** If disconnection of the throttle monitor switch is needed to start the engine, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service as soon as possible. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

### **WARNING**

Under no circumstances should disconnection of the throttle control wiring harness be used as a substitute for the monitor switch during normal operation of the snowmobile. Personal injury and damage could occur if the throttle system malfunctions or if the operator is unable to stop the engine in an emergency. If the snowmobile must be operated with a disconnected throttle control wiring harness, **EXTREME CAUTION MUST BE TAKEN. NEVER EXCEED 10 MPH WITH THE THROTTLE CONTROL WIRING HARNESS DISCONNECTED.**

■ **NOTE:** The monitor switch is now bypassed. All other ignition/electrical features (ignition switch, emergency stop switch, headlight, taillight, and brakelight) will operate properly.

## **Varying Altitude Operation**

Operating a snowmobile at varying altitudes requires changes in performance components. These changes affect drive train components (on certain models).

For altitude information, see the appropriate specifications sheet.



■ **NOTE: Just as important as calibrating the snowmobile for higher altitudes is recalibrating the snowmobile when going to lower altitudes.**

XF models (except the XF 800 High Country model) are initially set up at the factory for operation between 0-3000 feet.

F models are initially set up at the factory for operation between 0-5000 feet.

M models and the XF 800 High Country model are initially set up at the factory for operation between 6000-9000 feet.

■ **NOTE: Drive train changes can be made by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.**




## Lubrication

### Chain Case

■ **NOTE:** The snowmobile must be on a level surface for this procedure.

1. Check the lubricant level in the chain case by using the sight glass.



0746-115

■ **NOTE:** The correct level is when the lubricant is at least halfway up in the sight glass.


■ **NOTE:** Adding lubricant can be done by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

2. On the 800 cc models if the lube level is low, remove the fill plug from the chain case; then add the appropriate amount of Arctic Cat Synthetic Chain Lube (p/n 5639-038) in the fill hole. Install the plug.
3. On the 1100 cc models if the lube level is low, remove the three screws securing the shift actuator to the chain case, disconnect the actuator wiring harness, and remove the actuator w/extension; then add the appropriate amount of Arctic Cat Synthetic Chain Lube (p/n 5639-038) through the shift actuator opening. When the lube is halfway up the sight glass, install the shift actuator w/extension and connect the actuator wiring harness.

### CAUTION

When installing the shift actuator, rotate the actuator back and forth to properly align it with the extension gear. Failure to do so could cause component damage.

4. On the 1100 cc models, start the engine and verify proper reverse and forward operation.



PC019A

■ **NOTE:** If excessive build-up of moisture or discolored oil is detected in the chain case, it may be necessary to replace the chain lube.

■ **NOTE:** Replacing the lubricant can be done by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

To replace the lubricant, use the following procedure:

■ **NOTE:** The exhaust resonator must be removed for this procedure.

1. Place a drain pan on the floor beneath the snowmobile to allow the lubricant to drain from the chain case into the drain pan.
2. Remove the cap screws securing the chain case cover (with oil reservoir) to the chain case. Remove the cover and allow the oil to drain into the drain pan.

■ **NOTE:** It is critical that the snowmobile is on a level surface to ensure the lubricant drains properly and completely.



■ **NOTE:** Inspect the chain case cover seal for nicks or damage.

3. When the lubricant has completely drained from the case and the chain case is cleaned of old oil, properly seat the seal in the cover; then install the chain case cover. Tighten the cap screws to 100 in.-lb.
4. On the 800 cc models, pour recommended chain case lube into the fill hole until the lubricant is at least halfway up in the sight glass; then install the plug.
5. On the 1100 cc models, remove the three screws securing the shift actuator to the chain case, disconnect the actuator wiring harness, and remove the actuator w/extension. Pour recommended chain case lube through the shift actuator opening until the lubricant is at least halfway up in the sight glass; then install the shift actuator w/extension and connect the actuator wiring harness.

### CAUTION

**When installing the shift actuator, rotate the actuator back and forth to properly align it with the extension gear. Failure to do so could cause component damage.**

6. Install and secure the exhaust resonator.

■ **NOTE:** On the 1100 cc models, the resonator gasket(s) between the exhaust pipe(s) and resonator must be replaced.

7. On the 1100 cc models, start the engine and verify proper reverse and forward operation.

### CAUTION

**The correct lubricant to use in the chain case is Arctic Cat Synthetic Chain Lube. Any substitute may cause serious damage to the drive system.**


### Rear Suspension

This procedure should be done every 40 operating hours.

■ **NOTE:** Arctic Cat recommends that Arctic Cat All-Temp Grease (p/n 4639-365) be used for this procedure.

■ **NOTE:** Illustrated are the general locations of grease fittings. Actual locations will vary from model to model.

1. Shut engine off and wait for all moving parts to stop.
2. With the gas tank nearly empty (less than 1/4 full) and using Handlebar Stand (p/n 5639-152) or a suitable substitute, lay the snowmobile on its left side.
3. Remove ice and snow buildup from the skid frame to expose the grease fittings.



0746-093

4. Lubricate the grease fittings with all-temperature grease.



## Maintenance

Periodic Maintenance Checklist			
Item	Interval	Page	Remarks
Brake System	Daily	41	Check for binding, leakage, and proper operation; lever firmness, travel, caliper, disc, and pads
Cooling System - Liquid	Daily	14,35	Check for leakage, damage, obstructions, coolant level
Oil-Injection System	Daily	—	Check for leakage, damage, and injection/engine oil level
Engine Oil (1100 cc Non-Turbo Models)	2500 Mi/Seasonal	33	Change oil and filter
Engine Oil (1100 cc Turbo Models)	2000 Mi/Seasonal	33	Change oil and filter
Battery	Daily	14,38	Check for proper charge and tight connections
Stop Switch	Daily	—	Check for proper operation
Hoses	Daily	—	Check for damage, leakage, and wear
Headlight & Taillight/Brakelight	Daily	51-52	Check for proper operation and cleanliness
Steering System	Daily	—	Check for proper operation, tightness of bolts, and binding
Throttle Control System	Daily	26	Check for binding, sticking, proper operation, throttle cable tension, and wear
Drive Belt	Daily Monthly	44	Check for wear, cracks, and fraying Check length and width dimensions
Ski Wear Bars	Daily	52	Check for wear and damage
Electrical Wiring	Weekly	—	Check for wear, damage, and tight connections
Exhaust System	Weekly	14	Check for damage, leakage, and obstructions
Nuts, Bolts, Fasteners	Weekly	—	Check tightness
Recoil Starter	Weekly	—	Check rope for wear, fraying, and proper operation
Shock Absorbers	Weekly	17,49	Check for fluid leakage and damage and air pressure (Fox Air Shocks)
Spark Plugs	3500 Mi	35	Check center electrode insulator color, carbon, and gap
Valve Clearance (1100 cc Models)	5000 Mi/Seasonal	37	Check/adjust
Suspension	Weekly	48	Check for damage, loose components, and proper adjustment
Track Tension/Alignment	Weekly	46,47	Check/adjust as necessary
Wear Strips	Weekly	53	Check for wear and damage
Wires & Cables	Weekly	—	Check for wear, damage, and fraying
Fuel System - Tank, Pump, In-Line Filter, & Vent Hose	Weekly	—	Check for damage, wear, obstructions, and leakage
Fuel Filter (1100 cc Models)	5000 Mi/2 years	—	Replace
Air Silencer (800 cc Models)	Seasonal	—	Inspect/clean
Air Cleaner/Filter (1100 cc Turbo Models)	Weekly/Seasonal	32	Check/replace
APV System	Monthly	22	Check/adjust as necessary
Chain Case	Daily	29	Check lube level and for leakage
Chain Case - Lubricant	Seasonal	29	Replace
Heat Exchangers	Monthly	—	Check for wear, leakage, and damage
Drive Clutch/Driven Pulley	Monthly	16	Check for damage, binding, and wear/remove drive belt, clean drive clutch/driven pulley with compressed air, and clean sheaves with suitable parts-cleaning solvent
Rear Suspension	Monthly	30	Grease



The longevity and safety of the snowmobile can be increased by making periodic checks of the items in the preceding checklist.

If, at any time, abnormal noises, vibrations, or improper working conditions of any component of this snowmobile are detected, DO NOT OPERATE THE SNOWMOBILE. Take the snowmobile to an authorized Arctic Cat Snowmobile dealer for inspection and adjustment or repair. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

The snowmobile should be taken to an authorized Arctic Cat Snowmobile dealer at the end of each snowmobiling season for general inspection and for off-season storage servicing. This inspection and servicing is at the expense of the snowmobile owner.

### **Air Cleaner/Filter (1100 cc Turbo Models)**

The air filter inside the air cleaner housing must be kept clean to provide good engine power and gas mileage. If the snowmobile is used under normal conditions, inspect the filter weekly and replace the filter at the intervals specified. If operated in adverse conditions, inspect and service the filter more frequently. Use the following procedure to remove the filter and to inspect and/or replace it.

#### **CAUTION**

**Failure to inspect the air filter frequently if the snowmobile is used in adverse conditions can damage the turbocharger/engine.**

■ **NOTE:** For this procedure, the hood must be removed (see Access Panel/Hood (Removing/Installing) in the General Information section of this manual).

1. Remove the air filter from the housing.
2. Inspect the air filter for dirt or damage.

#### **CAUTION**

**Do not use compressed air in an attempt to clean the filter. Damage to the filter may occur. If the filter is dirty, it must be replaced.**

#### **CAUTION**

**A torn air filter can cause damage to the turbocharger/engine. Contaminants may get inside the turbocharger/engine if the filter is torn. Carefully examine the filter for holes or tears. Replace the filter with a new one if it is torn.**

3. Clean any debris from inside the air intake plenum.
4. Place the new filter (if necessary) into the housing.
5. Install the hood (see Access Panel/Hood (Removing/Installing) in the General Information section of this manual).

#### **CAUTION**

**Do not run the engine without the air filter installed. Severe damage to the turbocharger/engine will occur.**

### **Fuel System**

#### **⚠ WARNING**

**Whenever any maintenance or inspection is made on the fuel system in which there may be fuel leakage, there should be no welding, smoking, open flames, etc., in the area.**

### **In-Line Fuel Filter (1100 cc Models)**

Arctic Cat recommends that the in-line fuel filter be replaced every 5000 miles. The filter must be clean to allow the fuel hose to transmit the amount of gasoline required.

If the in-line fuel filter is obstructed, gasoline flow will be restricted; therefore, the filter must be replaced. To remove and install the in-line fuel filter, use the following procedure:

#### **⚠ WARNING**

**Since the fuel supply hose may be under pressure, always wear safety glasses; then remove the hose slowly to release the pressure. Place an absorbent towel around the connection to absorb the fuel.**

■ **NOTE:** Before removing the fuel filter, take note that the filter is directional and the arrow should be directed towards the engine.



■ **NOTE:** On the non-turbo models, the fuel filter is located below the steering support. To access the filter, the hood must be removed (see Access Panel/Hood (Removing/Installing) in the General Information section of this manual).

■ **NOTE:** On the turbo models, the fuel filter is located between the gas tank and the rear belt guard and is secured to the tunnel with a filter bracket. To access the filter, the left-side access panel must be opened and the lower console must be unlatched and opened.

1. Remove the hose clamps and discard; then slowly remove the fuel hoses from the fuel filter. Dispose of the excess fuel from the filter properly.
2. Inspect the fuel hoses thoroughly for any signs of cracking, cuts, or wear points.
3. Place the new hose clamps on the fuel hoses; then with the fuel pump inlet and outlet noted, connect the fuel hoses to the fuel filter. Secure with the hose clamps.

■ **NOTE:** After completing the changing of the fuel filter and the engine is started for the first time, inspect the filter area for any signs of leaks.

### Gasoline Additives

Fuel de-icer can be used for all models. Also, periodic use of an injector cleaner for 800 cc models is recommended especially in the last tank of gasoline before storage. Arctic Cat Fuel Stabilizer (p/n 0436-907) should also be added to the last tank of gasoline before storage.

### Fuel Pickup Valves


If ever there is a restricted fuel flow and a pickup valve is suspected, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

## Checking Engine Oil Level (1100 cc Models)

1. Park the snowmobile on a level surface; then start the engine and allow it to warm up for 5-10 minutes, or if the snowmobile was operated, allow the engine to idle for approximately 30 seconds.

■ **NOTE:** The snowmobile must be on a level surface for this procedure.

2. Shut the engine off; then remove the right-side access panel and verify oil is visible at least halfway up in the sight glass.



0746-166

3. If oil is not visible halfway up in the sight glass, add recommended engine oil until oil is visible halfway up the sight glass.

■ **NOTE:** Care must be taken not to over-fill the reservoir with oil.

## Changing Engine Oil/Filter (1100 cc Models)

### ⚠ WARNING

Care must be taken if a hot drain plug is removed by hand. Burning could occur.

■ **NOTE:** Recycle or properly dispose of the used engine oil.

■ **NOTE:** The access panels and hood must be removed for this procedure (see Access Panel/Hood - Removing/Installing in the General Information section).

1. Park the snowmobile on a level surface; then start the engine and allow it to warm up for 5-10 minutes, or if the snowmobile was operated, allow the engine to idle for approximately 30 seconds. Shut the engine off.




2. Remove the torx-head screws and the access plate from beneath the snowmobile.
3. Place a drain pan beneath the engine oil pan drain plug; then remove the plug and allow the oil to drain completely.



PC010A

4. Install the engine oil drain plug with a new gasket; then tighten the plug to 16 ft-lb.
5. Remove the four torx-head screws securing the right-side footrest to the tunnel and the support; then with a drain pan in position, remove the drain plug from the oil reservoir.



746-121A

■ **NOTE:** To aid in draining the oil from the reservoir, position a funnel between the reservoir and the opening of the tunnel running board.


6. After the oil has drained completely, install the drain plug with a new O-ring and tighten to 16 ft-lb.

■ **NOTE:** Always install a new Oil Pan Drain Plug Gasket (p/n 3402-011) and a new Reservoir Drain Plug O-Ring (p/n 1602-213) when changing the oil.

7. Using Oil Filter Wrench (p/n 0644-551), loosen (but do not remove) the oil filter and allow the oil to drain from the filter into the drain pan; then remove the filter.

■ **NOTE:** On the turbo models, the oil filter is accessible between the front opening of the chassis and the lower intercooler hose.

8. Apply a light coat of fresh engine oil to the seal of the new oil filter.
9. Install the new oil filter by turning the oil filter by hand until the seal has contacted the oil filter mounting surface; then tighten the oil filter to 15 ft-lb. Remove the drain pan.
10. Pour 2.9 l (3 U.S. qt) of the recommended engine oil into the oil reservoir.
11. Open the air bleed bolt located on the oil pump (beneath the coolant tank) to purge air from the oil hose.



PC016A

■ **NOTE:** When air can no longer be heard purging from oil pump bleed, tighten the bleed bolt to 7.5 ft-lb.

### CAUTION

**Do not attempt to start the engine with the bleed bolt open.**

12. Without starting the engine, place the handlebar emergency stop switch to the RUN position and the ignition switch to the ON position. The Oil Pressure Warning Icon should illuminate.

■ **NOTE:** If the warning icon does not illuminate, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

13. If the warning icon illuminates (from step 12), start the engine. The warning icon should go out within five seconds. If it does, proceed to step 14.



■ **NOTE:** If the warning icon does not go out, shut the engine off immediately and repeat step 11; then place the ignition switch to the ON position and repeat step 13. If the warning icon does not go out, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

14. Shut the engine off; then add oil to the oil reservoir until oil is visible halfway up in the sight glass.

15. Install the access plate and torx-head screws beneath the snowmobile; then install the hood and access panels (see Access Panel/Hood - Removing/Installing in the General Information section).

### Coolant Level

■ **NOTE:** Use a good quality, ethylene glycol-based, automotive-type coolant.

■ **NOTE:** Always check the coolant level with the engine cold.

### 800 cc Models

Open the left-side access panel and locate the coolant filler neck behind the steering support. The coolant should be visible at least 3/4-way to the top of the filler neck. If coolant must be added, the hood must be removed (see Access Panel/Hood - Removing/Installing sub-section in the General Information section).

#### CAUTION


After operating the snowmobile for the initial 5-10 minutes, stop the engine, allow the engine to cool down, and check the coolant level. Add coolant as necessary.

■ **NOTE:** On the HCR model if operating on ice or hard-packed snow, the ice scratchers must be engaged to reduce engine overheating.

### 1100 cc Models

■ **NOTE:** The access panels and hood must be removed for this procedure (see Access Panel/Hood - Removing/Installing sub-section in the General Information section).

1. Remove the filler cap from the coolant reservoir.
2. Verify the coolant level is at the bottom of the tab in the filler neck.



0746-117

3. If the coolant is below the tab, add coolant to the reservoir until at the tab.

#### CAUTION

If the coolant is below the tab and if coolant has been added, immediately inspect for leakage and/or damage. If leakage or damage is detected, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

■ **NOTE:** On the HCR model if operating on ice or hard-packed snow, the ice scratchers must be engaged to reduce engine overheating.

### Spark Plugs

#### 1100 cc Models

■ **NOTE:** Always use the recommended spark plugs in the engine. See the appropriate specifications sheet for correct spark plug gap.

Varying terrain conditions and operating usage may require spark plugs of a different heat range. For example, sustained cross-country riding will usually require colder heat-range spark plugs while trail riding or other continual slow speed operation will usually require hotter heat-range spark plugs.

#### CAUTION

If adjusting spark plug gap is necessary, do not use the center electrode as a leverage point. Damage to the plug may occur.



## Removing/Installing Spark Plugs

■ **NOTE:** Spark plug maintenance may be done by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

■ **NOTE:** For this procedure, the hood must be removed (see Access Panel/Hood (Removing/Installing) in the General Information section of this manual).

1. On the turbo models, remove the spark plug end caps; on the non-turbo models, remove the two cap screws securing the ignition coils to the cylinder head cover.
2. Using a 3/8-in. drive ratchet, adapter, and a 5/8-in. spark plug socket, remove the two spark plugs.

■ **NOTE:** Prior to installing the spark plugs, check the gap between the electrode and ground strap. The clearance should be 9 mm (0.035 in.).

3. Install the spark plugs. Tighten to 96 in.-lb.
4. On the non-turbo models, install the ignition coils onto the cylinder head cover and tighten the two 6 mm cap screws to 96 in.-lb. On the turbo models, install the spark plug end caps.
5. Install the hood (see Access Panel/Hood (Removing/Installing) in the General Information section of this manual).

## 800 cc Models

■ **NOTE:** Always use the recommended spark plugs in the engine. See the appropriate specifications sheet for correct spark plug gap.

Varying terrain conditions and operating usage may require spark plugs of a different heat range. For example, sustained cross-country riding will usually require colder heat-range spark plugs while trail riding or other continual slow speed operation will usually require hotter heat-range spark plugs.

## CAUTION

If adjusting spark plug gap is necessary, do not use the center electrode as a leverage point. Damage to the plug may occur.

## Removing/Installing Spark Plugs

■ **NOTE:** For this procedure, the hood must be removed (see Access Panel/Hood (Removing/Installing) in the General Information section of this manual).


1. Remove the springs securing the expansion chamber to the exhaust manifold and resonator.
2. Move the expansion chamber out of the way to access the spark plugs.
3. Remove the spark plug caps from the plugs.
4. Using a spark plug wrench, remove the plugs.
5. Install the plugs and finger-tighten.
6. Tighten the spark plugs to 19 ft-lb; then install the spark plug caps.
7. Place the expansion chamber into position and secure to the exhaust manifold and resonator with the springs.
8. Install the hood (see Access Panel/Hood (Removing/Installing) in the General Information section of this manual).

## Checking Spark Plugs

### 800 cc Models

To see if the spark plugs being used are of the proper heat range (after the snowmobile has been operated under normal driving conditions), remove the spark plugs and examine the condition of the center electrode insulator of each spark plug.





AO352A

- A. TAN or LIGHT BROWN insulator indicates correct spark plugs (heat range).
- B. LIGHT GRAY or WHITE insulator indicates over-heating of the engine. This condition is caused by a too lean condition or incorrect spark plugs (heat range too hot).
- C. BLACK insulator indicates fuel in the combustion chamber is not burning completely. This condition is caused by a too rich condition, too much oil, or incorrect spark plugs (heat range too cold).

■ **NOTE:** If the center electrode insulators are light gray, white, or black and if the oil-injection pump synchronization, and ignition timing are correct, different heat-range spark plugs may be necessary. Authorized Arctic Cat Snowmobile dealers have detailed spark plug information. Consult a dealer before changing spark plugs, as incorrect heat-range spark plugs could cause poor engine performance or engine damage.

### CAUTION

If a spark plug is light gray, white, or black and another is tan or light brown, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for inspection and service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

### Checking/Adjusting Valve Clearance (1100 cc Models)

After 5000 miles or prior to seasonal storage, valve clearance should be checked and adjusted as necessary.


■ **NOTE:** Take the snowmobile to an authorized Arctic Cat Snowmobile dealer for inspection and service. This service is at the discretion and expense of the snowmobile owner.

### CAUTION

It is critical that the checking/adjusting valve clearance be done at the recommended intervals or severe engine damage may occur.


### Checking/Adjusting APV Cables (800 cc Models)

Proper cable adjustment is critical to the operation of the APV system. Although inspecting cable adjustment is recommended every 1000-2000 miles, the cable should not need adjustment often. To check the cable adjustment, use the following procedure:



0745-819

1. Using a small needle-nose pliers, remove the servomotor cable holder.



0745-823

2. Using an adjustable wrench, rotate the servomotor actuator counter-clockwise to loosen the cable; then pull the cable housings down and out of the servomotor.



## CAUTION

Do not use the nut securing the pulley to the servomotor to rotate the actuator.

■ **NOTE:** For installing purposes, note the side that the servomotor cables are installed on.

3. Slide each cable drum out of the slot of the servomotor actuator.
4. While holding the cable housing firmly, pull the cable as far out as it will go; then release. Repeat three to four times. The cable/exhaust valve should move freely without binding.


■ **NOTE:** If the cable/exhaust valve does not move freely, the exhaust valve assembly will need to be removed for further inspection. Take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service.

■ **NOTE:** When measuring the cables, they are to be routed as close to their installed position as possible.

5. While holding the cable housing, lightly pull on one cable end to remove any slack; then measure the amount of exposed cable from the cable housing to the end of the cable (cable drum).

### APV CABLE LENGTH

800 cc	1.377 in. ± 0.039 in.
--------	-----------------------



0735-516

■ **NOTE:** The two cable measurements must be equal in length or less than 0.5 mm (0.020 in.) difference in length from each other.

■ **NOTE:** Repeat steps 4 and 5 for each cable; then compare the measurements to the APV Cable Length chart.

■ **NOTE:** The measurements must be within the specifications from the chart. If the measurements are within specifications, no adjustment is necessary (proceed to step 8). If they are not within specifications, proceed to step 6.

6. Loosen the jam nut on the cable to be adjusted; then using the adjusting nuts, lengthen or shorten the housing as needed.
7. Once the proper length has been attained, hold the adjusting nut in place and tighten the jam nut securely.
8. Place the cable housings into position in the servomotor. Secure the cable housings with the cable holder.

## CAUTION

Assure the cables are rotated and secured properly to avoid contacting exhaust components.

## Battery (Electric Start)

These sealed batteries after being in service require regular cleaning and recharging in order to deliver peak performance and maximum service life. The following procedures are recommended for cleaning and maintaining sealed batteries. Always read and follow instructions provided with battery chargers and battery products.

■ **NOTE:** Battery maintenance may be done by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

To remove and charge the battery, use the following procedure:

## ⚠ WARNING

Any time service is performed on a battery, the following must be observed: Keep sparks, open flame, cigarettes, or any other flame away. Always wear safety glasses. Protect skin and clothing when handling batteries. When servicing battery in enclosed space, keep the area well-ventilated.



**⚠ WARNING**

Battery posts, terminals, and related accessories contain lead and lead compounds, chemicals known to the state of California to cause cancer and reproductive harm. Wash hands after handling.

1. Remove the torx-head screw from the rear underside of the seat; then remove the seat.


**CAUTION**

On the LXR models, make sure to disconnect the seat heater harness connector prior to removing the seat.

2. Remove the negative battery cable and ground wire; then remove the positive cable.

■ **NOTE:** For installing purposes prior to removing the battery, note the routing and securing locations of the cables and harness wires.

3. Remove the two torx-head cap screws and lock nuts securing the battery bracket/solenoid to the seat-base; then move the bracket up and out of the way and remove the battery.



746-170A

**⚠ WARNING**

Avoid spillage and contact with skin, eyes, and clothing.

**CAUTION**

Do not charge the battery while it is in the snowmobile with the battery terminals connected.

4. Thoroughly wash the battery with soap and water; then using a wire brush, clean the battery posts and cable ends removing all corrosive buildup. Replace damaged cables or cable ends.

■ **NOTE:** If battery posts or cable ends have a build-up of white/green powder residue, apply water and baking soda to neutralize acid; then flush off with warm soapy water.

**CAUTION**

Do not remove seal strip on a sealed battery.

**⚠ WARNING**

Battery acid is harmful if it contacts eyes, skin, or clothing. Care must be taken whenever handling a battery.

5. Using a multimeter, test the battery voltage. The meter must read no less than 12.5 DC Volts for a fully charged battery.

■ **NOTE:** At this point if the meter reads as specified, the battery may be returned to service (see step 9).

6. If the meter reads less than specified voltage, charge the battery using the following guidelines.
  - A. When using an automatic battery charger, always follow the charger manufacturer's instructions.
  - B. When using a constant-current battery charger, use the following Battery Charging Chart.

**CAUTION**

Never exceed the standard charging rate.

**⚠ WARNING**

An overheated battery could explode causing severe injury or death. Always monitor charging times and charge rates carefully. Stop charging if the battery becomes very warm to the touch. Allow it to cool before resuming charging.



Battery Charging Chart (Constant-Current Charger)		
Battery Voltage (DC)	Charge State	Charge Time Required (at 1.5-2.0 Amps)
12.5 (minimum)	100%	None
12.2-12.4	75%-99%	3-6 hours
12.0-12.2	50%-74%	5-11 hours
11.0-11.9	25%-49%	13 hours (minimum)
11.5 or less	0-24%	20 hours (minimum)

■ **NOTE:** If the battery voltage is 11.5 DC Volts or less, some chargers may “cut off” and fail to charge. If this occurs, connect a fully charged booster battery in parallel (positive to positive and negative to negative) for a short period of time with the charger connected. After 10-15 minutes, disconnect the booster battery leaving the charger connected and the charger should continue to charge. If the charger “cuts off,” replace the battery.

- After charging the battery for the specified time, remove the battery charger and allow the battery to sit for 1-2 hours.
- Connect the multimeter and test the battery voltage. The meter should read no less than 12.5 DC Volts. If the voltage is as specified, the battery is ready for service.

■ **NOTE:** If voltage in step 8 is below specifications, charge the battery an additional 1-5 hours; then retest. The battery is ready for service.

- Place the battery into position in the snowmobile; then coat the battery posts and cable ends with a light coat of multi-purpose grease.

### CAUTION


Before installing the battery, make sure the ignition switch is in the OFF position.

- Connect the battery cables (positive cable first).

### CAUTION

Connecting cables in reverse (positive to negative and negative to positive) can cause serious damage to the electrical system.

■ **NOTE:** Assure the harness wires and cables are routed properly as noted during removing battery procedure.



- Install the battery bracket/solenoid and tighten the torx-head cap screws and lock nuts to 105 in.-lb; then install the seat and secure with the torx-head screw. Tighten securely.

■ **NOTE:** On the 1100 cc LXR models prior to lowering and securing the seat, connect the seat heater harness connector.

### Fuses


Fuses protect the snowmobile electrical system from overloading. If electrical parts in the snowmobile are not working, the system may have been overloaded and caused a blown fuse. Before repairing or replacing any electrical part, check the appropriate fuses. If a fuse blows (opens a circuit), all the parts of the snowmobile that use that circuit will not work.

Once which fuse to check has been determined, perform the following steps:


- Locate the fuse block and remove the fuse block cover.

■ **NOTE:** To locate the fuse block on the 1100 cc models, open the left-side access panel; the fuse block is on the belt guard. On the 800 cc models, open the right-side access panel; the fuse block is on the upper spar.





PC004A



PC020A

■ **NOTE:** There are spare fuses beneath the fuse block cover.

2. Remove the suspected fuse.

■ **NOTE:** Fuse function descriptions are next to the fuse contacts in the fuse block.

3. Look through the clear side of the fuse to see if the element inside is burned or separated. If it is, the fuse is blown and should be replaced with a fuse of the correct amperage rating.

### **WARNING**

**Always replace a fuse with one having the same specified amperage rating. Using a fuse with a higher rating can cause severe wire damage and could start a fire.**

4. Install the fuse block cover and close the access panel.

Even after replacing a fuse, it may continue to blow if the cause of the overload is not determined. If the fuse continues to blow, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

## **Brake System**


Arctic Cat recommends that the brake system (brake lever, fluid reservoir, hose, caliper, pads, and brake disc) be checked daily for fluid leakage, wear, or damage and for proper operation. Also, the brake fluid level must be checked every time before starting the engine.

### **WARNING**

**DO NOT operate the snowmobile when the brake lever lock is engaged or when any component in the brake system is damaged, worn, or adjusted improperly. If the snowmobile is operated and the brake system is not functioning properly, severe personal injury could result.**

## **Checking/Adding Brake Fluid**

1. With the brake fluid reservoir in a level position and the cover removed, check the fluid level. The brake fluid level must be at the high brake fluid mark in the reservoir.



0745-817

2. If the brake fluid is below the high brake fluid mark, add Arctic Cat approved DOT 4 brake fluid until the fluid is at the recommended level. Install and secure the reservoir cover. Do not allow moisture to contaminate the brake system.

### **CAUTION**

**Brake fluid is highly corrosive. Do not spill brake fluid on any surface of the snowmobile.**



### **⚠ WARNING**

Do not overfill the brake fluid reservoir. Overfilling the reservoir may cause the brake system to hydraulically lock. Use only Arctic Cat approved DOT 4 brake fluid. Never substitute or mix different types or grades of brake fluid. Brake loss can result. Brake loss can result in severe injury or even death.

### **Changing Brake Fluid**

The brake fluid must be changed on a regular basis and whenever the brake fluid has been overheated or contaminated. The brake fluid should be changed every 1000 miles or at the end of the snowmobiling season, whichever occurs first. Take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.


### **Checking Brake Lever Travel**

Before each use, check the brake lever travel using the following procedure:

1. Compress the brake lever fully.

■ **NOTE:** Do not pump the brake lever as it will produce an inaccurate reading.

2. Measure the distance between the brake lever and the handlebar. The distance must be greater than 2.54 cm (1 in.).



0745-816

3. If the resultant distance is less than specified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for service. If not under warranty, this service is at the discretion and expense of the snowmobile owner.

### **⚠ WARNING**

Do not operate the snowmobile if the compressed distance between the brake lever and the handlebar is less than 2.54 cm (1 in.). Brake loss may occur. Brake loss can result in severe personal injury.

### **Bleeding Brake System**

If the brake lever feels spongy when applied, the brake system may need to be bled. To bleed the brake, use the following procedure:

■ **NOTE:** The brake system may be bled by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

1. Remove the reservoir cover and (if necessary) fill the reservoir to the high brake fluid mark with Arctic Cat approved DOT 4 brake fluid.


### **CAUTION**

Brake fluid is highly corrosive. Do not spill brake fluid on any surface of the snowmobile.

### **⚠ WARNING**

Use only Arctic Cat approved DOT 4 brake fluid. Any substitute may result in a loss of brakes.

2. Slide a piece of flexible tubing over the ball of the bleeder valve and direct the other end into a container.



PC005A



3. Slowly compress the brake lever until maximum pressure is attained; then hold the lever in the compressed position to maintain pressure. Open the bleeder valve to release the fluid and air. When the fluid stops, close the bleeder valve; then release the brake lever.
4. Repeat step 3 until the brake fluid flows free of air bubbles.

■ **NOTE:** It may be necessary to refill the reservoir during the bleeding process. Never allow the brake fluid to go below the low brake fluid mark in the reservoir.

5. When the brake fluid is free of all air and the brake lever feels firm when compressed, fill the reservoir to the high brake fluid mark; then install and secure the cover. Remove the tube from the bleeder valve.

### Checking/Changing Brake Pads

The condition of the brake pads must be checked daily and changed if worn or damaged. To check and change the brake pads, use the following procedure:

■ **NOTE:** The brake pads may be changed by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

■ **NOTE:** When installing new brake pads, always install them as a set. Never install just one pad or use brake pads which have been used in another snowmobile.

1. Remove the brake fluid reservoir cover; then remove most of the brake fluid from the reservoir. Install the cover.

#### CAUTION

Brake fluid is highly corrosive. Do not spill brake fluid on any surface of the snowmobile.

■ **NOTE:** The above procedure will allow room for the fluid from the caliper when the pistons are pushed into the caliper for installing new brake pads. Replacing the cover will prevent fluid spillage.

2. Open the left-side access panel and remove the rear belt guard. Remove the driven pulley.
3. Remove the two torx-head screws securing the brake shield to the belt guard mount; then remove the cap screws securing the brake shield to the brake caliper.
4. Carefully move the shield out of the way; then remove the hairpin clip securing the brake pads to the caliper assembly.
5. Using a pair of pliers, pull the outer brake pad out of the caliper assembly.



■ **NOTE:** Changing one pad at a time will prevent one piston from pushing out the other piston from the caliper.

6. Measure the thickness of the brake pad. The brake pad thickness must be greater than 5.0 mm (0.20 in.). If the brake pad thickness is less than specified, replacement of both pads is necessary.



7. Using a flat-blade tool, slowly and carefully push the piston into the caliper.



8. Position the outer brake pad into the caliper; then install the hair-pin clip into the caliper assembly.
9. Repeat steps 5-8 for the inner pad; then secure the pad with the hairpin clip.
10. Remove the reservoir cover and remove the remaining fluid; then fill the reservoir with fresh fluid and install the cover.
11. Pump the brake lever to ensure correct positioning of the brake pads and proper brake lever travel (see Checking Brake Lever Travel sub-section); then release.

■ **NOTE:** If brake lever travel is not within specification, bleed the brake system (see Bleeding Brake System sub-section).

12. Remove the reservoir cover and fill the reservoir (if necessary) to the proper level with fresh brake fluid; then install the cover.
13. Secure the brake shield, the driven pulley (tightened to 20 ft-lb), and the rear belt guard; then close and secure the left-side access panel.

■ **NOTE:** When new brake pads are installed, a “burnishing” process is required (see Burnishing Brake Pads sub-section).

### Burnishing Brake Pads

After changing brake pads, the new brake pads must be burnished to achieve full braking effectiveness. Braking distance will be extended until brake pads are properly burnished.

To properly burnish the brakes, use following procedure:

1. Choose an area sufficiently large to safely accelerate to 30-40 mph and to brake to a stop.

■ **NOTE:** This procedure can also be accomplished using a shielded jack stand.

2. Accelerate to 30-40 mph; then compress brake lever to decelerate to a stop.

■ **NOTE:** Lightly apply the brake lever to come to an easy stop; do not over-apply brakes or “lock up” the track.

3. Repeat procedure 10-15 times allowing some cooling between stops.

■ **NOTE:** Do not repeat too soon or too aggressively as to get the brake disc “red hot.”

### **WARNING**

Do not attempt sudden stops or put yourself into a situation where a sudden stop will be required until the brake pads are properly burnished.

■ **NOTE:** This procedure stabilizes the pad material and extends the life of the pads.

### Drive Belt

The drive belt transfers power from the drive clutch to the driven pulley. If the belt is worn, cracked, or stretched, maximum power will not be transmitted and the belt could also fail and therefore must be replaced. Periodic checks (at least once a month under normal usage) of two drive belt specifications are essential.

1. Measure the outside circumference of the drive belt. The belt should be within the recommended range in circumference (see appropriate specifications sheet).
2. Measure the outside width of the drive belt. The belt should be within the recommended range in width.
3. Check the belt for cracking, fraying, etc.

If any of the specifications or conditions are unsatisfactory, replace the drive belt.

■ **NOTE:** Drive belts should be purchased from an authorized Arctic Cat Snowmobile dealer, as Arctic Cat drive belts are made to exact specifications and of quality material. Belts made by other manufacturers may not be of the same specifications or quality and, therefore, usage could result in poor performance and premature belt failure.

■ **NOTE:** Before starting the snowmobile in extremely cold temperatures, the drive belt should be removed and warmed up to room temperature. Once the drive belt is at room temperature, install the drive belt.




Also, new drive belts have a break-in period of approximately 25 miles. After installing a new drive belt, drive the snowmobile for 25 miles at 3/4 throttle or less. By revving the engine up and down (but not exceeding 60 mph), the exposed cord on the side of a new belt will be worn down. This allows the drive belt to gain its optimum flexibility and will extend drive belt life.

### CAUTION

Never run the engine with the drive belt removed. Excessive revving of the engine could result in serious engine damage and drive clutch failure.

### Checking/Adjusting Drive Belt Deflection



The drive belt must have the proper fit in the drive clutch and driven pulley. To check for proper drive belt fit, use the following procedure.

1. Place a straightedge on the top of the drive belt. The straightedge should reach from the drive clutch to the top of the driven pulley.

■ **NOTE: Make sure the drive belt is all the way out in the driven pulley before checking drive belt deflection.**

2. Using a stiff ruler centered between the drive clutch and driven pulley, push down on the drive belt just enough to remove all slack and note the amount of deflection. The deflection should be within the range of 28.5-31.8 mm (1 1/8-1 1/4 in.).
3. To correct drive belt deflection, remove the sheave adjuster from the pulley, remove or add shim washers to the adjuster, and install the adjuster.

■ **NOTE: Adding shim washers will decrease belt deflection and removing shim washers will increase belt deflection. Available shim washers from Arctic Cat are p/n 0648-714 (0.090 in.) - one included in the tool kit, p/n 0648-715 (0.030 in.), and p/n 0648-716 (0.060 in.).**

■ **NOTE: Removing/adding shim washers may be done by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.**


### Removing Drive Belt

■ **NOTE: Changing a drive belt can be done by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.**

1. Turn ignition key to the OFF position and wait for all moving parts to stop.
2. Set the brake lever lock.
3. Open the left-side access panel; then remove the rear belt guard.

■ **NOTE: On the 1100 cc models, move and secure the rear belt guard up and out of the way.**

4. Remove the cap screw, lock washer, washer, and sheave adjuster from the end of the driven pulley; then remove the sheave adjuster from the cap screw.





■ **NOTE:** Assure that the shims and O-ring are not removed from the adjuster.

5. Install the 2-in. flat washer (from the tool kit) onto the cap screw.
6. Install the cap screw into the driven pulley; then tighten the cap screw until the movable sheave opens far enough to allow the belt to be removed.
7. Remove the drive belt from the driven pulley first; then from the drive clutch.

■ **NOTE:** Before installing the drive belt, use a suitable cleaning solvent to thoroughly clean the sheaves.

### Installing Drive Belt

■ **NOTE:** If a new drive belt is being installed, see Drive Belt Break-In sub-section in the General Information section.

1. Place the drive belt (so the part number can be read) between the sheaves of the drive clutch first; then between the sheaves of the driven pulley.
2. Remove the cap screw; then remove the 2-in. flat washer from the cap screw.
3. Install the cap screw, lock washer, washer, and sheave adjuster back into the driven pulley. Tighten the cap screw to 20 ft-lb.
4. Install and secure the rear belt guard; then close the left-side access panel.

**⚠ WARNING**  
Never operate the snowmobile without the belt guard/access panel secured in place.

5. Release the brake lever lock.

### Track Tension

Track tension is directly related to the overall performance of the snowmobile. If the track is too loose, it may slap against the tunnel causing wear or it may “ratchet” on the track drive sprockets. If extremely loose, the idler wheels may climb over the track lugs forcing the track against the tunnel causing the track to “lock.” Arctic Cat recommends that the track tension be checked daily during the first 300 miles of operation and once a week thereafter and adjusted according to need. The track will stretch and take a “set” during break-in. Track deflection must be maintained within the recommended range.

**⚠ WARNING**  
Track tension must be properly maintained. Personal injury could result if a track is allowed to become excessively loose.


### Checking Track Tension

**⚠ WARNING**  
DO NOT attempt to check or adjust track tension with engine running. Turn ignition key to the OFF position. Personal injury could result from contact with a rotating track.


1. Remove excess ice and snow buildup from the track, track drive sprockets, and the inside of the skid frame.
2. Elevate the snowmobile on a shielded safety stand high enough to use a spring scale.
3. At mid-point of the track (on the bottom side), hook a spring scale around a track clip; then pull down on the scale to the recommended pressure. Measure the deflection (distance) between the bottom of the wear strip and the inside surface of the track clip. Compare the measurement with the chart.

Model	Setup Tension	After Break-In Tension
F/XF Models @ 20 lb	44-51 mm (1.75-2 in.)	51-57 mm (2-2.25 in.)
XF High Country Model @ 20 lb	51 mm (2 in.)	51 mm (2 in.)
M Models @ 15 lb	51 mm (2 in.)	51 mm (2 in.)





0743-188




0746-099

■ **NOTE:** On the M models, measurement is from the bottom of the wear strip at the point of the shock pad on the slide rail.

### Adjusting Track Tension

■ **NOTE:** To ensure proper track tension adjustment, perform all adjustments on both sides of the snowmobile.

1. Loosen the idler wheel axle cap screws.



0745-811

2. If the deflection (distance between the bottom of the wear strip and the inside surface of the track clip) exceeds specifications, tighten the adjusting bolts to take up excessive slack in the track.
3. If the distance between the bottom of the wear strip and the inside surface of the track clip is less than specified, loosen the adjusting bolts to increase the slack in the track.

## CAUTION

**Always maintain track tension within recommended specification.**

4. Check track alignment (see Track Alignment sub-section in this section).
5. After proper track tension is obtained, tighten the idler wheel axle cap screws to 34 ft-lb; then tighten the adjusting bolts securely against the axle.

■ **NOTE:** Since track tension and track alignment are interrelated, always check both even if only one adjustment seems necessary.

## WARNING

**Always make sure the adjusting bolts are snug against the axle and the idler wheel cap screws are tightened to specifications. Failure to do so could cause the track to become extremely loose and, under some operating conditions, allow the idler wheels to climb over the track lugs forcing the track against the tunnel causing the track to "lock." If a track "locks" during operation, severe personal injury could result.**

### Track Alignment

Proper track alignment is obtained when the rear idler wheels are equal distance from the inner track drive lugs. Excessive wear to the idler wheels, drive lugs, and track will occur if the track is improperly aligned. Arctic Cat recommends that the track alignment be checked once a week or whenever the track tension is adjusted.

### Checking Track Alignment

## WARNING

**Make sure the ignition key is in the OFF position and the track is not rotating before checking or adjusting track alignment. Personal injury could result if contact is made with a rotating track.**

1. Remove excess ice and snow buildup from the track, track drive sprockets, and the inside of the skid frame.



- Position the tips of the skis against a wall; then using a shielded safety stand, raise the rear of the snowmobile off the floor making sure the track is free to rotate.

### **WARNING**

The tips of the skis must be positioned against a wall or similar object.


### **WARNING**

**DO NOT** stand behind the snowmobile or near the rotating track. **NEVER** run the track at high speed when the track is suspended.

- Start the engine and accelerate slightly. Use only enough throttle to turn the track several revolutions. **SHUT ENGINE OFF.**

■ **NOTE:** Allow the track to coast to a stop. **DO NOT** apply the brake because it could produce an inaccurate alignment condition.


- When the track stops rotating, check the relationship of the rear idler wheels and the inner track drive lugs. If the rear idler wheels are centered between the inner track drive lugs, no adjustment is necessary.



- If the idler wheels are not centered between the inner track drive lugs, an adjustment is necessary.

### **Adjusting Track Alignment**

- On the side of the track which has the inner track drive lugs closer to the rear idler wheel, loosen the idler wheel axle cap screw; then rotate the adjusting bolt clockwise 1 to 1 1/2 turns.



- Check track alignment and continue adjustment until proper alignment is obtained.

■ **NOTE:** Make sure correct track tension is maintained after adjusting track alignment (see Track Tension sub-section in this section).

- After proper track alignment is obtained, tighten the idler wheel axle cap screw to 34 ft-lb; then tighten the adjusting bolts securely against the axle.

### **WARNING**

Always make sure the adjusting bolts are snug against the axle and the idler wheel cap screws are tightened to specifications. Failure to do so could cause the track to become extremely loose and, under some operating conditions, allow the idler wheels to climb over the track lugs forcing the track against the tunnel causing the track to "lock." If a track "locks" during operation, severe personal injury could result.

- Field test the track under actual conditions.
- After the field test, check the alignment of the track. If additional adjustment is necessary, repeat Adjusting Track Alignment procedure.

### **Suspension**

The suspension should be adjusted for the operational needs and riding preference of the operator.

The front shock springs determine the amount of ski pressure and the reaction of the front suspension to rough terrain. The amount of ski pressure can also be changed by adjusting the length of the skid frame front arm limiter straps.



On standard models, the rear arm shock absorber spring influences the load carrying capability of the snowmobile and should be adjusted for the weight and riding preference of the operator.


■ **NOTE:** On Sno Pro models, this adjustment is achieved by increasing or decreasing the air pressure in the rear arm air shock absorber.

### Adjusting Front (Ski) Shock Springs

The front (ski) shock springs are individually adjustable for the terrain conditions and driving style of the operator. The spring adjuster nut has been set at the factory so the correct amount of threads are exposed between the adjuster nut and the threaded shock body as an initial setting. Additional ski pressure can be obtained by tightening the spring tension; ski pressure can be decreased by relaxing spring tension.

■ **NOTE:** Equal adjustments should be maintained on both sides of the snowmobile.

Front (ski) shock spring pre-load adjustment is accomplished by loosening the adjuster nut locking collar (B) from the adjuster nut (A) and using the Spring Adjuster Tool from the tool kit, rotating the adjuster nut in whichever direction is desired. Tighten the locking collar against the adjuster nut.



### Adjusting Fox Air Shocks (Sno Pro Models)

■ **NOTE:** It is recommended to monitor the air pressure in the air shocks once every month.

■ **NOTE:** Adjusting air shocks may be done by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

The air shocks are individually adjustable for the terrain conditions and driving style of the operator. The shocks are preset at the factory (see chart) as an initial setting; however, it is possible to “fine tune” the shocks to match the operator’s weight, riding style, and terrain conditions.

Checking and adjusting air pressure must be done at riding temperature (outside). Also, it is advisable to check air pressure when the outside temperature varies more than 25°.

Initial Setting Chart		
Model	Front Shock (Ski)	Rear Arm Shock
M/XF Sno Pro Models	6.3 kg/cm <sup>2</sup> (90 psi)	10.2-10.6 kg/cm <sup>2</sup> (145-150 psi)
F Sno Pro Models	5.3 kg/cm <sup>2</sup> (75 psi)	N/A

■ **NOTE:** Care should be taken to have equal pressure in the front (ski) shocks before operating the snowmobile.

To increase or decrease air pressure, use the following procedure.

■ **NOTE:** When adjusting air pressure, all weight must be removed from the suspension, and the shock absorbers must be fully extended.

■ **NOTE:** Adding air pressure will increase the air spring force; reducing air pressure will decrease air spring force.

**⚠ WARNING**

**Do not exceed 10.5 kg/cm<sup>2</sup> (150 psi) in the shock.**

1. Remove the air valve cap from the shock.
2. Thread the valve of Shock Absorber Air Pump (p/n 2603-614) onto the shock air valve approximately six rotations.



■ **NOTE:** As the pump is being attached to the shock, the hose will fill with air. This will result in a lower gauge pressure 0.14-3.52 kg/cm<sup>2</sup> (2-5 psi).

3. To decrease air pressure in the shock, press the black bleed valve button half way down and hold until desired pressure is attained.

■ **NOTE:** Pressing the button fully down and releasing it will allow only a small amount of air to escape (micro-adjust).

4. To increase air pressure in the shock, pump until desired pressure is attained.
5. Remove the pump valve from the shock air valve.

■ **NOTE:** As the pump valve is being removed from the shock, the sound of air loss is from the pump hose, not from the shock.

6. Install the air valve cap onto the shock.

### Adjusting Skid Frame Front Arm

The skid frame front arm shock spring tension and the limiter straps are adjustable. However, Arctic Cat recommends that the shock spring be maintained at the factory preset of 1/8-1/4 in. preload. Tightening the skid frame front arm shock spring may cause improper balance and may ruin the handling features of the snowmobile.

The length adjustment of the front arm limiter straps determines the weight distribution between the front of the skid frame and the skis. Tightening the limiter strap (shortening the strap) will pull up on the front of the skid frame and will increase ski pressure. Loosening the limiter strap (lengthening the strap) lowers the front of the skid frame and decreases ski pressure.

When customizing the amount of ski pressure, be sure to adjust both straps equally and do not over-adjust the limiter straps to adversely affect steering and operator control of the snowmobile. Some experimentation may be required until the proper adjustment for the operator's individual style is obtained.

■ **NOTE:** If the limiter straps are adjusted, it is highly recommended that at least a minimum of 1/8 in. preload on the shock spring be maintained.

### **WARNING**

Do not adjust the front arm limiter straps to a point at which steering and operator control of the snowmobile are adversely affected.

### Adjusting Rear Spring Pre-Load (F Models)

Proper adjustment of rear spring pre-load is necessary to get the most desirable ride. The chart is designed to help in setting up rear spring pre-load; however, riding style is the single greatest factor in determining rear spring requirements.


Rider Weight (lb)	Cam Position
Up to 180	1
180-240	2
Over 240	3

■ **NOTE:** These cam position settings are suggestions only. Personal riding style will greatly influence cam position settings. Spend time to determine setting preferences.

Rear spring pre-load adjustment is accomplished by rotating the adjusting cams. Position 3 provides the stiffest ride, and position 1 is for the light driver or slow-speed trail riding. Position 2 is for the average operator under normal conditions. Always rotate the cam from the lighter position to the heavier position.

### **CAUTION**

Never force the adjustment cams from the low position to the high position. Cam damage may occur.



741-450A




To rotate an adjusting cam, use the spark plug wrench from the tool kit. Rotate the wrench until the cam is in the desired position. To stiffen the ride, rotate the cam so as to raise the spring end. Make the appropriate adjustment on the other cam.

### Adjusting Skid Frame Rear Arm Shock Spring (M/XF Models)

Proper adjustment of rear arm shock absorber spring pre-load is necessary to get the most desirable ride.

The rear arm shock spring is adjustable for the terrain conditions and driving style and weight of the operator. The spring adjuster nut has been set at the factory so the correct amount of threads are exposed between the adjuster nut and the threaded shock body as an initial setting.

Rear spring pre-load adjustment is accomplished by loosening the adjuster nut locking collar (B) from the adjuster nut (A) and using the Spring Adjuster Tool from the tool kit, rotating the adjuster nut in whichever direction is desired. Tighten the locking collar against the adjuster nut.




### Lights

For the correct headlight bulb and/or taillight/brakelight LED, see the appropriate specifications sheet.

### Removing and Installing Taillight/Brakelight

These models are equipped with an LED taillight/brakelight. If the LED fails, it must be replaced. To remove and install the LED, use the following procedure.




746-097A

1. Disconnect the taillight harness connector.
2. Remove the two torx-head screws securing the taillight to the bracket.
3. Connect the taillight harness connector; then secure the taillight to the bracket with the two torx-head screws.

### Removing/Installing Headlight Bulb

■ **NOTE:** The bulb portion of headlight is fragile. **HANDLE WITH CARE.** When replacing the headlight bulb, the bulb assembly must first be removed from the housing. Do not touch the glass portion of the bulb. If the glass is touched, it must be cleaned with a dry cloth before installing.

1. Disconnect the headlight harness connector from the bulb; then remove the rubber grommet from the headlight housing.
2. Rotate the bulb retainer counter-clockwise until it unlocks from the housing; then remove the bulb.



0746-096

3. Install the bulb and retainer; then rotate the retainer clockwise until it properly locks in place.
4. Install the rubber grommet; then connect the headlight harness connector to the bulb.



5. Check headlight aim (see Adjusting Headlight Aim in this sub-section).

### **⚠ WARNING**

**Do not operate the snowmobile unless headlight beam is adjusted properly. An incorrectly adjusted beam will not provide the operator the optimum amount of light.**


### **Adjusting Headlight Aim**

The headlight can be adjusted for vertical aim of the HIGH/LOW beam. The geometric center of HIGH beam zone is to be used for vertical aiming.

1. Position the snowmobile on a level floor so the headlight is approximately 8 m (25 ft) from an aiming surface (wall or similar surface).


■ **NOTE:** There should be an “average” operating load on the snowmobile when adjusting headlight aim.

2. Measure the distance from the floor to midpoint of the headlight.
3. Using the measurement obtained in step 2, make a horizontal mark on the aiming surface.
4. Make a vertical mark which intersects the horizontal mark on the aiming surface directly in front of the headlight.
5. Engage the brake lever lock and start the engine. Move the headlight dimmer switch to the HIGH beam position. DO NOT USE LOW BEAM.
6. Observe the headlight beam aim. Proper aim is when the most intense beam is centered on the vertical mark 5 cm (2 in.) below the horizontal mark on the aiming surface.



0745-813

7. Adjust the headlight using the adjusting screw on the backside of the headlight housing until correct aim is obtained. Shut the engine off; then disengage the brake lever lock.



PC014A

### **Ski Wear Bars**

The ski wear bar is a replaceable bar attached to the underside of the ski. The purpose of the wear bar is to assist in turning the snowmobile, to minimize ski wear, and to maintain good steering control. If the snowmobile is operated primarily in deep snow, ski wear bar wear will be minimal; however, if the snowmobile is operated on terrain where the snow cover is minimal, the ski wear bar will wear faster. To maintain positive steering characteristics, Arctic Cat recommends that the ski wear bars be checked before each use and replaced if worn beyond 1/2 of the original diameter. Ski wear bars are available from an authorized Arctic Cat Snowmobile dealer.

### **⚠ WARNING**


**Operating the snowmobile with excessively worn ski wear bars may result in a loss of steering control.**

### **Removing Ski Wear Bars**

■ **NOTE:** Determine which type of wear bar is being replaced and remove and install accordingly.

1. Remove ice and snow buildup from the ski.
2. Using a suitable safety stand or lift, elevate the front of the snowmobile.
3. Remove the lock nuts securing the wear bar to the ski.





0743-185

4. Remove the wear bar from the ski.

### Installing Ski Wear Bars

1. Move the wear bar into position on the bottom of the ski.

■ **NOTE:** If installing a double-offset wear bar, the carbide edge should be directed to the outside of the ski.

2. Align the wear bar studs with the holes in the ski; then install the lock nuts. Tighten to 11-15 ft-lb.

### Adjusting Ski Stance (M/XF Models)

■ **NOTE:** Local laws and/or regulations as to maximum width of the ski stance on these snowmobiles may be applicable. Always comply with the maximum width laws and/or regulations when adjusting ski stance.

■ **NOTE:** Ski stance can be increased/decreased by 2.5 cm (1.0 in.).


1. Place the front of the snowmobile on a support stand.
2. Remove the cotter pin; then remove the slotted nut and cap screw securing the ski assembly to the spindle. Remove the ski. Account for the rubber damper, inserts, and washers.
3. To increase ski stance, place both ski stance spacers to the outside of the spindle.
4. To decrease ski stance, place both ski stance spacers to the inside of the spindle.
5. Apply an all-temperature grease to the non-threaded portion of the cap screw; then slide the cap screw through the ski accounting for the rubber damper, inserts, and washers.

■ **NOTE:** Install the cap screw so the slotted nut will be located to the inside of the ski.

6. Apply red Loctite #271 to the threads of the cap screw; then tighten the nut to 45 ft-lb.
7. Place the cotter pin into the ski cap screw and spread the pin.
8. Repeat procedure for the other ski.

### Rail Wear Strips

Arctic Cat recommends that the wear strips be checked weekly and replaced as necessary. Measure the wear strips at 25.4 cm (10 in.) intervals. Wear strips must be 10.7 mm (0.42 in.) thick or thicker.



0745-807

If wear strip measurements are less than specified, replacement of both wear strips is necessary to prevent premature track clip wear and possible track damage. Take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

Each time a new set of wear strips are installed, they should be tempered. Temper the wear strips by driving the snowmobile for approximately a mile on a hard pack trail; then immediately drive into deep snow and allow the wear strips to cool. Repeat the procedure (warming up the wear strips; then cooling them down) two or three times.

■ **NOTE:** The rail wear strips will wear rapidly if the snowmobile is operated on terrain on which the snow cover is minimal. Loose snow is required to cool and lubricate the wear strips and prevent accelerated wear.



## Performance Tips

Operating a high performance snowmobile requires a special attention that is not required by a low performance snowmobile. Often, a minor adjustment will result in a large increase in performance. This section is intended to highlight minor conditions that adversely affect performance and the adjustments needed to correct them. Be sure, however, to thoroughly read and understand this entire manual especially the section on spark plugs, track tension and alignment, and suspension.


**DRIVE BELT** — This link between the engine and drive train is often the most neglected component. The drive belt must have the proper fit in the drive clutch and driven pulley. Proper fit is when the top surface of the drive belt is flush with the top or up to 1/16 in. higher than the driven pulley sheaves (with the sheaves fully closed). If drive belt deflection is above specification, the snowmobile will bog and lack power at engagement and will have a slower maximum speed. For good performance, proper belt deflection is critical. To correct this condition, first determine if the drive belt is within specifications (see Drive Belt sub-section) and replace if worn or too long. Always run the drive belt in the same direction. Installing the drive belt so the part number can be read will ensure that the drive belt is always run the same direction.

**DRIVE BELT DEFLECTION** — Drive belt length, condition, and deflection are all important for peak performance. To check and adjust drive belt deflection, remove the belt guard; then use the following procedure.

■ **NOTE:** It may be necessary to remove a shim washer from between the driven pulley sheaves to allow the driven pulley to close tighter. Adding shim washers will decrease belt deflection and removing shim washers will increase belt deflection. Available shim washers from Arctic Cat are p/n 0648-714 (0.090 in.) - one included in the tool kit, p/n 0648-715 (0.030 in.), and p/n 0648-716 (0.060 in.).

■ **NOTE:** Removing/adding shim washers may be done by the snowmobile owner if qualified to do so. If the owner does not feel qualified, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for this service. This service is at the discretion and expense of the snowmobile owner.

1. Turn the engine off; then open the access panel.
2. Make sure the drive belt is sitting at the top of the driven pulley sheaves.
3. Place a straightedge on top of the drive belt. The straightedge should reach from the driven clutch to the top of the driven pulley.
4. Using a stiff ruler centered between the drive clutch and driven pulley, push down on the drive belt just enough to remove all slack. Note the amount of deflection on the ruler at the bottom of the straightedge. The deflection should be at 1 1/4 in.



■ **NOTE:** Push down on the belt with the ruler only until the bottom of the belt flexes upward; then read the amount of deflection.

5. To correct drive belt deflection, remove the sheave adjuster from the pulley, remove or add shim washers to the adjuster, and install the adjuster.

■ **NOTE:** Adding shim washers will decrease belt deflection; removing shim washers will increase belt deflection.

6. Install the belt guard; then close the access panel.



**DRIVE CLUTCH AND DRIVEN PULLEY** — Keeping the drive clutch and driven pulley clean should be the primary consideration of the operator. The drive clutch and driven pulley can be cleaned of any drive belt accumulation using compressed air. The sheaves can be cleaned using a clean cloth and parts-cleaning solvent.

**DRIVE CLUTCH/DRIVEN PULLEY OFFSET** — If premature drive belt wear is experienced or if the drive belt turns over, offset must be checked. Also, offset must be checked whenever either the drive clutch or driven pulley is serviced.


■ **NOTE:** For checking offset, it is necessary to use Clutch Alignment Bar (p/n 0644-428) to obtain a drive clutch/driven pulley offset of 1.485 in. This special tool can be purchased from an authorized Arctic Cat snowmobile dealer.

To check offset, use the following procedure.

1. Open the left-side access panel; then remove the belt guard.
2. Install the clutch alignment bar between the drive clutch sheaves.
3. Allow the bar to rest on the drive clutch shaft and against the outside edge of the driven pulley stationary sheave.

■ **NOTE:** The alignment bar must extend beyond the front edge of the drive clutch.

4. With the bar against the outside edge of the driven pulley stationary sheave at points A and B, the bar should just clear the inside edge of the stationary sheave of the drive clutch and rest on the stationary shaft at point C with a maximum 0.060 in. clearance at point C. At this point, measurement between points A and C should be 1.507 in. (with a maximum 0.060 in. clearance). If the bar either will not clear the inside edge or is more than the specified amount, the offset must be corrected.



0745-177

■ **NOTE:** If the offset is out of specification, take the snowmobile to an authorized Arctic Cat Snowmobile dealer for drive system evaluation and/or servicing. This service is at the discretion and expense of the snowmobile owner.

**GASOLINE** — On the 800 cc and turbo models for optimum performance, use 91 octane (minimum) gasoline.



## Preparation for Storage

Prior to storing the snowmobile, it must be properly serviced to prevent corrosion and component deterioration. An authorized Arctic Cat Snowmobile dealer should perform this service; however, the owner/operator can perform this service if desired. This service is at the discretion and expense of the snowmobile owner. To prepare the snowmobile for storage, Arctic Cat recommends the following procedure:

1. Clean the seat cushion with a damp cloth and a Vinyl Protectant.
2. Clean the snowmobile thoroughly by hosing dirt, oil, grass, and other foreign matter from the skid frame, tunnel, hood, and belly pan. Allow the snowmobile to dry thoroughly. DO NOT get water into any part of the engine.

■ **NOTE:** On the 1100 cc models, change the engine oil and replace the air filter if necessary; then proceed to step 6.

### CAUTION

**Do not do steps 3-5 on the 1100 cc models; severe engine damage could result.**

3. Place the rear of the snowmobile up on a shielded safety stand.
4. Carefully pry the intake boots partially over the throttle body inlets; then start the engine and allow to idle.
5. Spray an Engine Storage Preserver into the intakes until the engine exhaust starts to smoke heavily or until the engine starts to drop in RPM. Turn engine off. Install the intake boots.

### CAUTION

**Do not run the engine without the belt guard in place and secured.**

6. Plug the exhaust system outlet with a clean cloth.

### CAUTION

**Do not do step 7 on the 1100 cc models; severe engine damage could result.**

7. With the ignition switch in the OFF position:

A. Disconnect the high tension leads from the spark plugs; then remove the plugs, connect them to the leads, and ground them on the cylinder heads.

### CAUTION

**Never crank the engine over without grounding the spark plugs. Damage to coils and ECU may result.**

- B. Pour 29.5 ml (1 fl oz) of SAE #30 petroleum-based oil into each spark plug hole and pull the recoil starter handle slowly about 10 times.
- C. Install the spark plugs and connect the high tension leads.
8. Fill the gas tank to its rated capacity; then add Arctic Cat Fuel Stabilizer (p/n 0436-907) to the gas tank following directions on the container for the stabilizer/gasoline ratio. Tighten the gas tank cap securely.
9. With the snowmobile level, check the lubricant level in the chain case. If low, add chain lube through the fill plug hole.
10. Remove the drive belt from the drive clutch/driven pulley. Lay the belt on a flat surface or slide it into a cardboard sleeve to prevent warping or distortion during storage.
11. Clean and inspect the drive clutch and driven pulley.
12. Apply light oil to the upper steering post bushing and shafts of the shock absorbers.
13. Lubricate the rear suspension with all-temperature grease.
14. Tighten all nuts, bolts, and cap screws making sure all nuts, bolts, and cap screws are tightened securely. Make sure all rivets holding the components together are tight. Replace all loose rivets.



15. Clean and polish the hood, console, and chassis with Cat Cleaner (p/n 4639-371). DO NOT USE SOLVENTS. THE PROPELLANT WILL DAMAGE THE FINISH.

■ **NOTE:** On electric start models, disconnect the battery cables making sure to disconnect the negative cable first; then clean the battery posts and cables. Charge the battery.

#### **CAUTION**

Sealed batteries require charging if left for extended non-start periods. Arctic Cat recommends trickle charging once a month. Follow the manufacturer's instructions and cautions.

16. If possible, store the snowmobile indoors. Raise the track off the floor by blocking up the back end making sure the snowmobile is secure. Loosen the track adjusting bolts to reduce track tension. Cover the snowmobile with a machine cover or a heavy tarpaulin to protect it from dirt and dust.

17. If the snowmobile must be stored outdoors, position the snowmobile out of direct sunlight; then block the entire snowmobile off the ground making sure the snowmobile is secure. Loosen the track adjusting bolts to reduce track tension. Cover with a machine cover or a heavy tarpaulin to protect it from dirt, dust, and rain.

#### **CAUTION**

Avoid storing in direct sunlight and using a plastic cover as moisture may collect on the snowmobile causing corrosion.



## Preparation after Storage

Taking the snowmobile out of storage and correctly preparing it for another season will assure many miles and hours of trouble-free snowmobiling. Arctic Cat recommends the following procedure:

1. Clean the snowmobile thoroughly. Polish the exterior of the snowmobile.
2. Clean the engine. Remove the cloth from the exhaust system. Check exhaust system and air-intake silencer for obstructions.
3. Inspect all control wires and cables for signs of wear or fraying. Replace if necessary. Use cable ties or tape to route wires and cables away from hot or rotating parts.
4. Inspect the drive belt for cracks and tears. Check belt specifications. Replace if damaged or worn. Install the drive belt.

■ **NOTE: If the old belt is worn but in reasonable condition, retain it with the snowmobile as a spare in case of emergency.**

5. Inspect all fuel hoses and oil hoses for deterioration or cracks; replace if necessary. Make sure all connections are tight; then on the 800 cc models, fill the oil-injection reservoir with the recommended 2-cycle oil (see Gasoline-Oil - Recommended Injection Oil sub-section in the General Information section).

■ **NOTE: After prolonged storage of the 800 cc models, Arctic Cat recommends one tankful of 100:1 gas/oil mixture be used in conjunction with the oil-injection system to ensure proper lubrication.**

6. On the 800 cc models, inspect the spark plugs. Replace, gap, or clean as necessary.
7. Tighten all nuts, bolts, and cap screws making sure all nuts, bolts, and cap screws are tightened securely.
8. If not done during preparation for storage, lubricate the rear suspension with all-temperature grease.
9. Check the coolant level and all coolant hoses and connections for deterioration or cracks. Add properly mixed coolant as necessary.
10. On electric start models, charge the battery until fully charged (see Battery sub-section in the Maintenance section); then connect the battery cables making sure to connect the positive cable first. Test the electric start system.
11. Inspect the entire brake system, all controls, headlight, taillight, brakelight, ski wear bars, and headlight aim; adjust or replace as necessary.
12. Adjust the track to the proper tension and alignment (see Track Tension and Track Alignment sub-sections in the Maintenance section).



## **U.S. EPA Emission Control Statement/Warranty Coverage (U.S. Only)**

### **STATEMENT/WARRANTY**

Arctic Cat warrants to the original retail purchaser, and each subsequent purchaser, that all U.S. EPA-certified Arctic Cat snowmobiles are designed, built, and equipped to conform to all U.S. EPA Emission Control Regulations. Please read the following information completely.

Your authorized Arctic Cat snowmobile dealer will repair or replace any defective emission-related component at no cost to you during the warranty period. You may have non-warranty service performed by any repair establishment that uses equivalent components. The regulations provide significant civil penalties for tampering that causes your snowmobile to no longer meet U.S. EPA emission standards.

Arctic Cat further warrants that the engine and its emission-related components are free from defects in materials or workmanship that could cause the engine to fail to comply with applicable regulations during the warranty period.

If you have any questions about this information, or the emission warranty coverage statement, contact your local authorized Arctic Cat snowmobile dealer.

### **WARRANTY PERIOD**

The emission warranty period for this snowmobile begins on the same date as the standard warranty coverage and continues for 30 months or 2500 miles, whichever comes first.

### **COMPONENTS COVERED**

The emissions warranty covers major emissions control components and emission-related components listed as follows:

#### **Engine Management and Sensors**

Barometric Pressure Sensor  
Camshaft Position Sensor  
Engine Control Unit (ECU)  
Engine Coolant Temperature Sensor  
Intake Air Temperature Sensor  
Manifold Absolute Pressure Sensor  
Oxygen Sensor  
Throttle Position Sensor

#### **Ignition System**

Ignition Coil  
Knock Sensor System  
Crankshaft Position Sensor  
Exhaust Temperature Sensor  
Capacitive Discharge Ignition (CDI) Module  
Magnet Pick-Up

#### **Fuel/Air System**

Fuel Injectors  
Fuel Pressure Regulator  
Fuel Pump  
Carburetor(s)  
Turbocharger Assembly  
Air Bypass Valve  
Turbo Waste Gate Control Valve  
Crankcase Ventilation System  
ISC Valve

#### **Miscellaneous Items Used in Aforementioned Systems**

Connectors  
Switches  
Grommets  
Clamps  
Hoses  
Ties  
Gaskets  
Wiring

### **OWNER'S RESPONSIBILITIES**

The owner of any snowmobile warranted under this Arctic Cat Emission Control Statement is responsible for the proper maintenance and use of the snowmobile as stated in the Operator's Manual. Proper maintenance generally includes replacement and service, at the owner's choosing, such items as air filter, oil and oil filter, or any other part, item, or device related to emissions control as specified in the Operator's Manual. It is the owner's responsibility to ensure that the snowmobile is used in a manner for which it was designed.



## **NOTES**



### **Change of Address, Ownership, or Warranty Transfer**

Arctic Cat Inc. keeps on file the current name and address of the owner of this snowmobile. This will allow Arctic Cat to reach the current owner with any important safety information which may be necessary to protect customers from personal injury or property damage. Please make sure a copy of this form is completed and returned to Arctic Cat Inc. if you move or if the snowmobile is sold to another party.

This form may also be used to transfer the unused portion of the original warranty to a second party. In order to transfer warranty, fill out this form completely; then return a copy of this form to Arctic Cat Inc. Arctic Cat will then process the application and issue warranty for the balance of the time remaining of the original warranty.

- ☐ Address Change
- ☐ Ownership Change
- ☐ Warranty Transfer

### **CHANGE OF ADDRESS/OWNERSHIP/ WARRANTY TRANSFER TO:**

Name \_\_\_\_\_

Address \_\_\_\_\_

City/State (Province)/Zip Code (Postal Code) \_\_\_\_\_

Phone # (    ) \_\_\_\_\_

Year and Model Snowmobile \_\_\_\_\_

Vehicle Identification Number (VIN) \_\_\_\_\_



Fold Back Once

**CHANGE OF ADDRESS/OWNERSHIP**

Place  
Stamp  
Here

**ARCTIC CAT INC.  
PRODUCT SERVICE AND  
WARRANTY DEPT.  
P.O. BOX 810  
THIEF RIVER FALLS, MN 56701**



### **Warranty Procedure/Owner Responsibility**

At the time of sale, an Owner Registration form is to be completed by the selling dealer and consumer. The receipt of the registration form by Arctic Cat is a condition precedent to warranty coverage. It is the selling dealer's responsibility to retain and/or submit the appropriate copies of the form to the appropriate place(s) to initiate warranty coverage.

The dealer will furnish to the consumer a signed copy of the form which must be presented to the dealer when requesting warranty service. **The registration form is the consumer's proof of ownership and warranty eligibility. The form is used by the dealer to validate the warranty claim.** Retain your copy of the form and keep it in a safe place.

When warranty repair is suspected, the snowmobile should be taken to the selling dealer, who has the primary responsibility to perform warranty repairs. Subject to the limitations set forth in the Limited Warranty, in the event the selling dealer has ceased to do business, you have moved, or you are in a location away from your selling dealer, warranty may be performed by any authorized Arctic Cat Snowmobile dealer.

The authorized Arctic Cat Snowmobile dealer will examine the snowmobile or part to determine if, in his opinion, a warrantable condition exists. If a warrantable condition appears to exist, the dealer will repair or replace, at Arctic Cat's option, free of charge, including any related labor costs, all parts that are found to be warrantable and any other parts which the warrantable part caused to be damaged. You, the consumer, will then be asked to sign a warranty form to ensure Arctic Cat that the warranty work was actually performed.

It is the consumer's responsibility to maintain and service the snowmobile in accordance with Arctic Cat's recommendations in the Operator's Manual. To protect yourself and your snowmobile, follow all safety and service tips. **Arctic Cat will NOT warrant repairs required as a result of not performing standard operator maintenance, storage procedures, and service as outlined in the Operator's Manual.**

Should you have any questions concerning the warranty, contact an authorized Arctic Cat Snowmobile dealer.

Arctic Cat Inc., P.O. Box 810, Thief River Falls, MN 56701 (218) 681-8558



